

UNIT STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240
P. O. BOX 1933

Form approved.
Budget Bureau No. 1004-0-100
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-18498

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Anderson 7 Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cato San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 7. T-9S, R-30E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐
2. NAME OF OPERATOR
Harvey E. Yates Company
3. ADDRESS OF OPERATOR
P. O. Box 1933, Roswell, NM 88201
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FNL & 1980' FEL

14. PERMIT NO

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

4041.2 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Existing: 8 5/8" csg, set @ 896', cement circulated.

CIBP @ 3230'.

Perfs - 4 @ 3223'.

Procedure:

1. Set CIBP @ 3200' with 35' cement plug on top.
2. Cut and pull approximately 2600' 5 1/2" csg.
3. Set 100' plug @ 2650' (50' inside and 50' outside of 5 1/2" csg). *Tag plug.*
4. Set 100' plug @ 946' (50' inside and 50' outside of 5 1/2" csg). *" "*
5. Set 50' surface plug. Install dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED *Layne Collins*

TITLE Production Analyst

DATE 2/26/87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
PETER W. CHESTER
DATE

JAN 30 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side