

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of the electrically drilled wells, true vertical depth shall also be reported. For multiple completions, from 30 through 34 shall be reported for each zone. The form is to be filled in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Rustler 1836	T. Emory XX Marker 8539	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 3 Brothers 8838	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2374	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 3168	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3579	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta 4916	T. McKee	Base Greenhorn	T. Granite
T. Paddeco	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb 6484	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 7345	T. Bone Springs	T. Wingate	T.
T. Wolfcamp LM 8491	T. Bough A 9064	T. Chinle	T.
T. Penn.	T. Bough B 9098	T. Permian	T.
T. Cisco (Bough C)	T. Bough C 9138	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	176	176	Surface Rock	DST #1	4310-4358'	(48')	San Andres: TO 30";
176	1375	1199	Rock, Redbeds	SI 60"			TO 45"; SI 180". Opened with strong
1375	1890	515	Redbeds, Anhydrite				blow, increased to 5# in 15 min and stabi-
1890	3125	1235	Anhy, Salt				lized at 6# in 20 mins. Reopened tool with
3125	3645	520	Anhy				strong blow, decreased from 6" in bucket in
3645	3873	228	Anhy, Dolo				20 mins to 3/4" in bucket in 36 mins.
3873	4720	847	LS, Sh, Dolo				RECOVERY: 2890' water, CL 18000. SAMPLER:
4720	4980	260	LS, Dolo, Cht, anhy				2700 cc water, 1200 psi, BHT: 122°. PRESSURES:
4980	7420	2440	Dolo, Sh, Sd, Anhy				IHP 1860, IFP 393-1310, ISIP 1350, FFP 1284-
7420	7920	500	Shale				1362, FSIP 1362, FHP 1860.
7920	8120	200	Shale, Dolo				
8120	8480	360	Sh, Dolo, Anhy				
8480	9475	995	LM, Sh, Cht				