

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-1348	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Cola ADO State Com
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. X 2
4. Location of Well UNIT LETTER E, 1880 FEET FROM THE North LINE AND 760 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 8S RANGE 33E NMPM.		10. Field and Pool, or WHdcat Bar U Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4394.6' GR		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 9475'. Ran 236 joints 5-1/2" P-110 23# casing set 9475'. Regular guide shoe set 9475', float collar set 9433'. Cemented w/980 sacks Class H with .9% CE-14 and 10% salt (yield 1.19, weight 15.8). PD 5:45 AM 7-5-87. Bumped plug to 2500 psi, released pressure, float and casing held okay. WOCU.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Production Supervisor DATE 7/7/87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY JUL 9 1987 DATE JUL 9 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JUL 8 1987
OCD
HOBBS OFFICE

1987 JUL 8

U.S. DEPARTMENT OF JUSTICE
FEDERAL BUREAU OF INVESTIGATION