

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1348	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name	
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Cola ADO State Com	
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 2	
4. Location of Well UNIT LETTER <u>E</u> <u>1880</u> FEET FROM THE <u>North</u> LINE AND <u>760</u> FEET FROM THE <u>West</u> LINE, SECTION <u>31</u> TOWNSHIP <u>8S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Bar U Penn	
15. Elevation (Show whether DF, RT, GR, etc.) 4394.6' GR		12. County Chaves	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1603.

Spudded 17-1/2" hole at 12:30 PM 6-10-87. Ran 11 jts 13-3/8" 54.5# J-55 casing set 375'. 1-Notched guide shoe set 375', insert float set 340'. Cemented with 400 sx Class "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 11:15 PM 6-10-87. Bumped plug to 350 psi, released pressure and float held okay. Drilled out 1:30 PM 6-11-87. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Jerry Sexton TITLE Production Supervisor DATE 6/12/87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUN 15 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JUN 15 1987
OCO
HOBBS OFFICE