

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N. M. OIL CONS. COMMISSION
SUBMIT IN TRIPLI
Other Instructions
verse side
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.
NM 31/12

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT— for such proposals.)

1. WELL NO. X OTHER _____
NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FWL, Sec. 25-T14S-R30E

14. PERMIT NO.

API #30-005-21066

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

4013' GR

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hodge AEF Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit K, Sec. 25-T14S-R30E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

Spudded with rathole 9:00 PM 8-29-87. Resumed drilling with rotary rig 10:15 AM 8-30-87
12-1/4" hole. Ran 19 joints 8-5/8" 24# J-55 set 820'. 1 Texas pattern notched guide
shoe set 820', insert float set 777'. Cemented w/516 sacks Class "C" with 2% CaCl (yield
1.32, weight 14.8). PD 2:15 PM 8-31-87. Bumped plug to 750 psi, released pressure and
float held okay. Cement circulated 100 sacks to pit. WOC. Drilled out 5:15 AM 9-1-87.
WOC 18 hrs. NU and tested. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED Anita Dodditt
(This space for Federal or State office use)

TITLE Production Supervisor

DATE 9-1-87

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

*See Instructions on Reverse Side

