Form 3160-5 (Nevember 1983) (Formerly 9-331)	UN' D STATES N. M. OL CONSTITUTION DEPARTMEN. OF THE INTERIORO BOX 1980 HONT BUREAU OF LAND MANAGEMENTHOBBS, NEW MEXIC	5. LEASE DESIGNATION AND SEBIAL SU
(Do not use th	INDRY NOTICES AND REPORTS ON WELLS bis form for proposals to drill or to deepen or plug back to a different reservoir Use "APPLICATION FOR PERMIT " for such proposals.)	6 IF INDIAN, ALLOTTRE OR TRIBE NAME
1. OIL GAS WELL WELL 2. NAME OF OFEBATOR	L OTHER Dry Hole	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
Maralo, In 3. ADDRESS OF OPERA	ΠC	Federal 8
P. O. Box 4. LOCATION OF WELL See also space 17 h At surface	832, Midland, Texas 79702 0832 (Report location clearly aut in accordance with any State requirements.* below.)	10. FIELD AND POOL OR WILDCAT Wildcat
460' FSL a	and 660' FEL of Section 8	11. SEC., T., B., M., OR BLE. AND SURVEY OB AREA
14. PERMIT NO.	15 BLEVATIONS (Show whether DP, RT. GR. etc.) 4226.5 GL	Sec. 8, T.10.S, R.31 E 12. COUNTY OF PARISH 13. STATE Chaves New Mexico
16.	Check Appropriate Box To Indicate Nature of Notice, Reponsion Structure of Intention To:	ort, or Other Data subsequent apport or:

		Sebsadorit matori os.		
	۲ ۲		r	
TEST WATER SHUT-OFF PUL	L OR ALTER CASING WATER	B SHUT-OFF	BEFAIRING WELL	
FRACTURE TREAT	LTIPLE COMPLETE FBACT	UBE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE ABA	NDON* SHOOT	TING OR ACIDIZING	ABANDONMENT* X	
REPAIR WELL CH.	ANGE PLANS (Other	-)		
(Other)		NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) •

10-06-87 Plugging procedure verbal from Mr. Peter Chester w/BLM.

RU Dowell & pumped 70 sx Class "C" cement plug from 3240' to 3140' (100' plug). Tagged plug @ 3120'. Ran 50 sx Class "C" cement plug from 1978' to 1878' (100' plug). Pumped 85 sx cement plug from 1450' to 1300' (in & out bottom of 8 5/8" casing @ 1400'). Tagged cement plug @ 1275'. Pumped 15 sx cement plug from 50' to surface. Cut off well head and installed dry hole marker. Cleaned up location.

	BUREAU OF THE BU	
18. I hereby certify that the foregoing is save an	1d correct	
SIGNED BUINDA CAPM	Agent Agent	DATE October 12, 1987
(This space for Federal or State office use)		
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE Approved as to plugging of the well bors Liability under bond is retained until surface restoration is completed.	PETER W. CHESTER OCT 1 6 1987
	*See Instructions on Reverse Side	1 1
Title 18 U.S.C. Section 1001, makes it a cr United States any false, fictitious or fraudu	rime tor any person knowingly and willfully to mal alent statements or representations as to any mati	ke to any demeriment stouble of the



•--