

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N. M. OIL CONS. COMMISSION

P. O. BOX 1980

HOBBS, NEW MEXICO 88240
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-32408	
2. NAME OF OPERATOR Read & Stevens, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 1518, Roswell, NM 88202		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FNL & 1980' FEL		8. FARM OR LEASE NAME Cedar Point Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4076' GL		10. FIELD AND POOL, OR WILDCAT Cedar Point Strawn	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 27-15S-30E	
		12. COUNTY OR PARISH Chaves	13. STATE NM

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETION	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT* <input checked="" type="checkbox"/>
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged 6-1-88.

RU Halliburton, set plugs as follows:

Surf plug:	50'-surf
13 3/8	550'-450'
Salt	915'-815'
8-5/8	3317'-3217'
Glorietta	4830'-4730'
Abo	6855'-6705'
Bough C	9165'-9015'
Atoka	10644'-10444'

Install dry hole marker, cleaned up location.

Notified 5-26-88 by John C. Maxey.

18. I hereby certify that the foregoing is true and correct

SIGNED

John C. Maxey Jr.

TITLE

Petroleum Engineer

DATE

6-17-88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

APPROVED
PETER W. CHESTER

JUN 21 1988

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA