N. M. OIL CONS. COMMISSION — P. O. BOX 1980

5 0 <b>22</b> 1		. BOX 1980	W.00 00010	Form Approved.		
Form 9-831 Dec. 1973		BS, NEW ME	XICO 88240	Budget Bureau N	o. 42-R1424	
	D STATES		5. LEASE			
DEPARTMENT OF THE INTERIOR			NM 31112			
GEOLOGIC	CAL SURVEY	SURVEY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AN	7. UNIT AGREEMENT NAME					
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)			8. FARM OR LEASE NAME			
1. oil gas other dry hole			Yates-Federal 9. WELL NO.			
2. NAME OF OPERATOR	1					
Dalport Oil Corp	oration		10. FIELD OR WILL	CAT NAME		
3. ADDRESS OF OPERATOR	Hildcat SE Chares Qu gas arewass					
1401 Elm St. #34	11. SEC., T., R., M., OR BLK. AND SÜRVEY OR AREA 35-145-30E					
4. LOCATION OF WELL (REPOR						
below.) AT SURFACE: 660 F	S & WL		12. COUNTY OR P		TF	
AT TOP PROD. INTERVAL: Same			Chaves	NI		
AT TOTAL DEPTH: same			14. API NO.		· ·	
16. CHECK APPROPRIATE BOX	TO INDICATE NATURE	OF NOTICE,	30-005-2	21076		
REPORT, OR OTHER DATA	an-re	- Carlo Carlo	15. ELEVATIONS	(SHOW DF, KDB	, AND WD)	
REQUEST FOR APPROVAL TO:	SUBSEQUENT RE	PORT OF:	4012 KB		<del> </del>	
TEST WATER SHUT-OFF	<b>□</b>	_		·.		
FRACTURE TREAT	<b></b>		1			
SHOOT OR ACIDIZE	H		(MOTE: December 1			
REPAIR WELL PULL OR ALTER CASING	H		(NOTE: Report result change on I	res of multiple comp Form 9–330.)	netion or zone	
MULTIPLE COMPLETE	Ö		4.	2 -		
CHANGE ZONES		s.ex	<i>,</i>			
ABANDON*			S. A.			
(otner)			a service and the service and			
17. DESCRIBE PROPOSED OR C including estimated date of measured and true vertical d	OMPLETED OPERATION itarting any proposed wo epths for all markers and	S (Clearly state ork. If well is d I zones pertinen	e all pertinent detail irectionally drilled, gi it to this work.)*	s, and give pert ive subsurface lo	inent dates, cations and	
TD 2535' verbal	approval to p	lug giver	n by Peter C	hester on	7-30-88.	
Halliburton will	plug as foll	ows:				
2535-2435' 25 sx	. 100' plua (	TD)				
1640-1540 25 sx	, 100' plug					
815-715 25 sx	, 100' plug (	across su	ırface shoe	at 765')		
Surface - 50 foo	t pluq. Tag	gged plug	]			
Will clean locat	ion, level pi	ts and er	rect 4' stee	el marker.		
Subsurface Safety Valve: Manu. a	nd Type			Set @	Ft.	
18. I hereby certify that the foreg	oing is true and correct					
· 1	TITLE GO	eoloaist	DATE 8-	1-88		
	<u> </u>					
	(This space for Fe	ederel or State off	ice use)	(La	220VED	

APPROVED BY \_\_\_\_\_\_ TITLE \_\_\_\_\_ CONDITIONS OF APPROVAL, IF ANY:

APPROVED
PETER W. CHESTER

AUG 24 1988

BUREAU OF LAND MANAGEMENT ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side

RECEIVED

AUG 29 1988

OCTO MORRA OFFICE