

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1501	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy	1608	T. Strawn	LS 11948	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	Salado	T. Atoka	12230	T. Pictured Cliffs		T. Penn. "D"	
B. Salt	2742	T. Miss	Austin Cycle 13170	T. Cliff House		T. Leadville	
T. Yates		T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3580	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Otzte	
T. San Andres	4417	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta	5896	T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blinberry		T. Delaware Sand		T. Todilto		T.	
T. Tubb	7166	T. Bone Springs		T. Entrada		T.	
T. Drinkard		T. XX Marker	9763	T. Wingate		T.	
T. Abo	7804	T. Seaman	LS 11014	T. Chinle		T.	
T. Wolfcamp	LS 9501	T. Morrow	LS 12693	T. Permian		T.	
T. Penn	10123	T.		T. Penn "A"		T.	
T. Cisco (Bough C)							
T. ABO SHALE	7902						

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface, Rock	10250	10670	420	Sh, LS, Dolo
40	409	369	Redbeds	10670	12080	1410	Sh, LS
409	2500	2091	Anhy, Redbeds	12080	13250	1170	Sh, LS, SS
2500	2640	140	Salt				
2640	2730	90	Salt, Sh, Sd, Anhy				
2730	2820	90	SS, Sh, Anhy				
2820	3590	770	Sh, Anhy				
3590	4390	800	Sh, Anhy, Dolo				
4390	4410	20	Sh, Anhy, dolo, SS				
4410	5860	1450	Dolo				
5860	6020	160	LS				
6020	6130	110	Anhy, Sh				
6130	7170	1040	Dolo				
7170	7320	150	Dolo, Sh				
7320	7860	540	Dolo				
7860	8460	600	Dolo, Anhy, Sh				
8460	8700	240	Dolo				
8700	9080	380	Dolo, Sh, Anhy				
9080	9490	410	Dolo				
9490	9760	270	LS				
9760	10250	490	LS, Sh				

RECEIVED

JUL 19 1991


HOBBS OFFICE