

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-21147
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-4061
7. Lease Name or Unit Agreement Name Coachman State
8. Well No. 1
9. Pool name or Wildcat SE Chaves Queen Gas Area Assoc.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Drilling Company
3. Address of Operator 105 South 4th Street, Artesia, NM 88210
4. Well Location Unit Letter <u>A</u> : <u>660</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line

Section 23 Township 12S Range 31E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
4421' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-22-97 Drilled plug and resumed drilling.  
4-27-97 TD 3100'. Reached TD at 11:45 AM, 4-27-97.  
4-29-97 Ran 76 jts. 5 1/2" 15.5# casing, set at 3084.18'.  
Cemented with 400 sxs. Premium Plus Halliburton Lite + 5#/sx. salt + 1/4# flocele (yield 2, weight 12.8). Tailed in with 200 sxs. Premium Plus 50/50 Poz mix +5/10% Halad-322 + 5# salt (yield 1.39, weight 13.9). Plug down at 9:34 PM, 4-29-97. Bumped plug to 600 psi, held okay. Circulated trace of cement to pit. WOC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leskman TITLE Engineering Technician DATE 5-1-97

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR TITLE  DATE MAY 12 1997

CONDITIONS OF APPROVAL, IF ANY:

4567891011121314  
▲  
N.Y. 1997  
Received  
Harris  
CCC