

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-21147
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-4061
7. Lease Name or Unit Agreement Name Coachman State
8. Well No. 1
9. Pool name or Wildcat SE Chaves Queen Gas Area Assoc.
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4421' GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Yates Drilling Company	
3. Address of Operator 105 South 4th Street, Artesia, NM 88210	
4. Well Location Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line Section 23 Township 12S Range 31E NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4421' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole at 10:30 AM, 4-21-97.

4-21-97 Ran 10 jts. 8 5/8", 24# J-55 casing, set at 416'. Cemented with 250 sxs. Premium + HCL cement, 6# sx. Gilsonite + 1/4# Flocele. Tailed in with 250 sxs. Premium + 2% CaCL. Bumped plug to 200 PSI, held okay. Cement did not circulate. Ran temp. survey, cement at 80' below surface. Notified NMOCD of 1". Pumped 200 sxs. Premium + 3% CaCL. Circulated 30 sxs. to pit. WOC. Drilled out at 4:30 PM, 4-22-97. Reduced hole and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leshman TITLE Engineering Technician DATE 4-30-97

TYPE OR PRINT NAME \_\_\_\_\_ TELEPHONE NO. \_\_\_\_\_

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAY 02 1997

CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_