

SURFACE USE AND OPERATING PLAN

Page 2

- B. The average grade will be less than 1%.
- C. No turnouts are planned.
- D. No culverts, cattleguard, gates, low-water crossings, or fence cuts are necessary
- E. Surfacing material will consist of native caliche. Any caliche found on location will be utilized first. If additional caliche is needed, then, it will be obtained from the nearest BLM-approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor, Sweatt Construction Company.
- F. The proposed access road as shown in Exhibit #3 has been centerline flagged by John West Engineering.

3. Location of Existing Wells:

Exhibit #4 shows all existing wells within a one-half mile radius of this well.

4. Location of Existing and/or Proposed Facilities:

- A. If the well is productive, a tank battery will be installed on the location and will probably consist of one or two 300 bbl storage tanks situated on the south side of the pad surrounded by a 24" earthen berm. A heater treater and separator will be located in the southwest corner of the pad.
- B. If the well is productive, oil and artificial lift devices are required (pumpjack) then a propane engine will be used to power the pumpjack.
- C. If the well is productive, rehabilitation plans are as follows:
 - (1) The reserve pit will be back-filled after the contents of the pit are dry (within 10 months after the well is completed).
 - (2) Topsoil removed from the drill site will be used to recontour the pit area and any unused portions of the drill pad to the original natural level, as nearly as possible, and reseeded as per BLM specifications.

5. Location and Type of Water Supply:

The well will be drilled with a combination brine and fresh water mud system as outlined in the drilling program. The water will be obtained from commercial water stations in