

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-005-21153
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Drickey Queen Sand Unit
8. Well No. 56
9. Pool name or Wildcat Caprock Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4185' GL; 4198' DF; 4200' KB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Injection
2. Name of Operator Queen Sand Operating Co.
3. Address of Operator 13760 Noel road, Suite 1030. LB44 Dallas, Tx 75240
4. Well Location Unit Letter D : 130 Feet From The North Line and 380 Feet From The West Line Section 15 Township 14S Range 31E NMPM Chaves County

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER: set 5 1/2" casing <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 2086'. KOP @ 2411 1/4° to 3086' 87.6° 184.10° AZM, TVD 2811.11'.
Ran 5 1/2" as follows: 5 1/2" 17# 3042.56'
float collar 2.00'
shoe joint 42.03'
guide shoe 1.00'
Set @ KB 3087.59'

Cemented by BJ as follows: 203 sks "C" + 3#salt + 16% gel
170 sks "C" super modified + 9/10% FL-50 + 4/10% CO-32
Bumped plug w/73 BOW, circ 18sks to pit. Plug down @ 10:30 1/2/00 held OK. WOC 24hrs
before drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James L Hull, Jr. TITLE Production Clerk DATE 7/27/00
TYPE OR PRINT NAME James L Hull, Jr. TELEPHONE NO. 972-383-8260

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE AUG 21 2000

CONDITIONS OF APPROVAL, IF ANY:

