

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-005-21153
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Drickey Queen Sand Unit
8. Well No.	56
9. Pool name or Wildcat	Caprock Queen

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Injection	
2. Name of Operator Queen Sand Operating Co.	
3. Address of Operator 13760 Noel road, Suite 1030, LB44 Dallas, Tx	
4. Well Location Unit Letter D : 130 Feet From The North Line and 380 Feet From The West Line Section 15 Township 14S Range 31E NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4185' GL; 4198' DF; 4200KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well 12/27/99. Drill 12 1/4" hole to 415' Ran 8 5/8' 26# casing as follows:
8 5/8" 26# 375.04'
float collar 1.80'
shoe joint 41.55'
TPN shoe 1.20'
Set @ KB 419.59'

Cemented by BJ as follows: 65 sks "H" + 10% A10B + 10% gil = 2% CaCl + 1/4 gil
250 sks "C" + 2% CaCl

Bump plug with 22 BOW. Held. Plug down @ 0735 1/28/00. Circ 35 sks to pit.
WOC 24 hrs before drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James L Hull, Jr. TITLE Production Clerk DATE 7/27/00
TYPE OR PRINT NAME James L Hull, Jr. TELEPHONE NO 972-383-8260

(This space for State Use)

APPROVED BY GARY WINK DATE 7/27/00

CONDITIONS OF APPROVAL, IF ANY: