

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-005-21154
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Injection	7. Lease Name or Unit Agreement Name Drickey Queen Sand Unit
2. Name of Operator Queen Sand Operating Co.	8. Well No. 57
3. Address of Operator 13760 Noel road, Suite 1030, LB44 Dallas, Tx	9. Pool name or Wildcat Caprock Queen
4. Well Location Unit Letter <u>A</u> : <u>140</u> Feet From The <u>North</u> Line and <u>330</u> Feet From The <u>East</u> Line Section <u>15</u> Township <u>14S</u> Range <u>31E</u> NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4276' GL; 4289' DF; 4291' KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>set surface casing</u> <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well 1/11/2000. Drill 12 1/4" hole to 410'. Run 8 5/8" 26# csg:
8 5/8" 26# 369.88'
float collar 1.65'
shoe joint 46.42'
TPN shoe 1.00'
Total tools & casing 418.95' - set @ KB

Cemented by BJ Services as follows: 65 sks "H" + 10% AlOB + 10# gil + 2% CaCl + 1/4# CF
250 sks "C" + 2% CaCl

Bumped plug w/23 1/2 BOW. Plug held. Plug down @ 03:37 1/12/2000. WOC 24 hrs before drlg
(Circulated 30 sks to pit)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <u>James L Hull, Jr.</u>	TITLE <u>Production Clerk</u>	DATE <u>7/27/00</u>
TYPE OR PRINT NAME <u>James L Hull, Jr.</u>		TELEPHONE NO <u>972-383-8260</u>

(This space for State Use)

APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		