

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-005-21155

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

7. Lease Name or Unit Agreement Name
Drickey Queen Sand Unit

2. Name of Operator
Queen Sand Operating Co.

8. Well No. 58

3. Address of Operator
13760 Noel Road, Suite 1030, LB44 Dallas, TX 75240

9. Pool name or Wildcat
Caprock Queen

4. Well Location
Unit Letter F : 2470' Feet From The North Line and 2640' Feet From The West Line
Section 15 Township 14S Range 31E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4259' GL; 4271 KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: <u>surface pipe</u> <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9 5/8" 38# RIII ST&C API

1) Tex ptrn guide shoe (1)	1.00'
2) Shoe joint (1)	45.05'
3) Float collar (1)	2.25'
4) 9 5/8" 38# (8)	360.59'
Total tools & casing	408.89'
Cut off	15.00'
Set @ GL	393.00'
Set @ KB	403.00'

Cemented with 65 sks H + 10% A10B + 2% CaCl + 10% gil + 1/4# celo flakes.
200 sks C + 2% CaCl2. Bump plug with 27bbbls water. Plug down @ 00:45 1/26/00. Circulate 35 sks to pit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James L Hull, Jr. TITLE Production Clerk DATE 6/20/00
TYPE OR PRINT NAME James L Hull, Jr. TELEPHONE NO. 972-383-8260

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT SUPERVISOR

CVI

74

