

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-005-21157
5. Indicate Type of Lease Federal <input type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Drickey Queen Sand Unit
8. Well No. 55
9. Pool name or Wildcat Caprock Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4258' GL; 4268' DF; 4270' KB

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Injection
2. Name of Operator Queen Sand Operating Co.
3. Address of Operator 13760 Noel Road, Suite 1030, LB44 Dallas, TX 75240
4. Well Location Unit Letter M : 330 Feet From The West Line and 140 Feet From The South Line Section 15 Township 14S Range 31E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4258' GL; 4268' DF; 4270' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: cement 5 1/2" casing <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 3170'. KOP @ 2510' 0° to 3170' @ 85.5 @ 355.20 AZM, TVD 2926.20'.  
Ran 5 1/2" 17# csg as follows:  
73 jts of 5 1/2" float collar 3128.43'  
show joint 2.00'  
guide shoe 43.46'  
Total tools & casing 1.00'  
3174.89'

Cementex by BJ as follows: 203 sks "C" + 3# salt + 16% gel  
170 sks "C" super "C" modified + 9/10% FL-50 + 4/10% CO-32.

Bump plug with 73 BOW. Held-plug dwn @ 1300 12/17/99. WOC 24 hrs before drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James L Hull, Jr. TITLE Production Clerk DATE 7/27/00

TYPE OR PRINT NAME James L Hull, Jr. TELEPHONE NO. 972-383-8260

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY CHRIS WILLIAMS DATE JAN 04 2001

CONDITIONS OF APPROVAL, IF ANY: DISTRICT SUPERVISOR