

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Yates Drilling Company

3. Address and Telephone No.

105 South 4th Street, Artesia, NM 88210 505-748-4500

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

750' FNL & 1000' FWL Section 34-12S-31E D

NM-0256521

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cactus Queen Unit #16

9. API Well No.

30-005-21159

10. Field and Pool, or Exploratory Area

SE Chaves Queen Gas

11. County or Parish, State

Chaves, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 20" hole, 8-25-00

8-31-00 Resumed drilling 11:30 pm, 8-31-00.

9-2-00 Ran 11 jts. 8 5/8" 24#, J-55 ST&C casing, set at 460'. Texas Pattern Guide Shoe, set at 460'. Float collar set at 417.76'. Cemented with 63 sxs. 35/65/5 + 5# Gilsonte (yld 1.86, wt 12.7). Tailed in with 220 sxs. Class "C" + 2% CaCl2 (yld 1.34, wt 14.8). PD at 11:51 am, 9-1-00. Bumped plug to 1000 psi, float did not hold. Circulated 78 sxs. to pit. Shut in at surface. WOC 16 hrs.

ORIG SGD: GARY GOURLEY

14. I hereby certify that the foregoing is true and correct

Signed Karen J. Leshman

Title Engineering Technician

Date 9-8-00

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____