

NO. OF COPIES RECEIVED	
DISTRIBUTION	
AMOUNT	
DATE	
BY	
REMARKS	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL GAS WELL OTHER- Injection Well

Name of Operator
Vega Petroleum Corporation

Address of Operator
P. O. Box 2383, Midland, Texas 79702

Location of Well
UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM
THE West LINE, SECTION 6 TOWNSHIP 13-S RANGE 32-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4388' DF

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

7. Unit Agreement Name No. 1
No. Caprock Queen Unit

6. Farm or Lease Name
No. Caprock Queen Unit

9. Well No.
Tract 17, Well No. 4

10. Field and Pool, or Wildcat
Caprock Queen (Lea)

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/></p> <p>DRILL OR ALTER CASING <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p> <p>PLUG AND ABANDON <input type="checkbox"/></p> <p>CHANGE PLANS <input type="checkbox"/></p>	<p>SUBSEQUENT REPORT OF:</p> <p>REMEDIAL WORK <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/></p> <p>CASING TEST AND CEMENT JOBS <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p> <p>ALTERING CASING <input type="checkbox"/></p> <p>PLUG AND ABANDONMENT <input checked="" type="checkbox"/></p>
---	---

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Displaced hole with 2500# per 100 bbls. salt base mud.
2. Set CIBP at 2750'.
3. Set 100' cement plug on top of CIBP.
4. Cut off and pulled 5-1/2" casing at 1000'.
5. Spotted 35 sx. cement plug in-and-out of 5-1/2" casing stub.
6. Spotted 40 sx. cement plug in-and out of 9-5/8" surface casing stub.
7. Spotted 10 sx. cement plug at surface and erected a 4-1/2" regulation dry hole marker.
8. Cleaned up location for NMOCC inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY Betty W. Kettanow TITLE Manager DATE 11-4-77

APPROVED BY John W. Runyan TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: