

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

March 24, 1948

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
**Cities Service Oil Company** State **"R"** Well No. **3** in the \_\_\_\_\_  
 Company or Operator

**C SE NW** of Sec. **17**, T. **13S**, R. **32E**, N. M. P. M.,  
**Caprock** Field, **Lea** County.

The dates of this work were as follows: **March 16<sup>th</sup>, 18 and 19, 1948**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **March 15** 19 **48**  
 and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was drilled to a T. D. 3070'. 5 1/2" casing was set at 3032.47' and cemented with 600 sacks. The hole was loaded with heavy mud and bottom of hole was cemented with 25 sacks by Halliburton Oil Well Cementing Company. Tubing pulled and 5 1/2" casing was shot off at 1000' and again at 780', recovering 780' of 5 1/2" casing. Spotted 20 sacks of cement in open hole at 700' and spotted 20 sacks inside 8 5/8" to top of cellar leaving 4' marker of 4" pipe bull plugged.

Witnessed by **R. W. Ely** **Cities Service Oil Company** **District Superintendent**  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

**24th** day of **March**, 19 **48**Name **[Signature]**Position **District Superintendent**Representing **Cities Service Oil Company**  
Company or OperatorAddress **Drawer G., Hobbs, New Mexico**My commission expires **March 12, 1951**

Remarks:

APPROVED

MAR 2 6 1948

**[Signature]**  
 Name  
**OIL & GAS INSPECTOR**  
 Title