

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

WELL RECORD

Mail to Qil Conservation Commission, Santa Pe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

### H. L. Tileon Drilling Compeny ### Hilling Fox 1517 Continental - State waln No. 1 n. Field NVb fee 18 n. 13-5	LOGA	AREA 640 A TE WELL C	CRES	_l	it with (?). UNTIL FOR		IPLICATE. FORM ROPERLY FILLEI		NOT BE A	PPROVED	
Continental - Table Walls Mark Walls Mark Captook Mark Capto		H. L.	Wilson								
Sale Least N. M. F. M. General 1980 feet south of the North line and 1980 feet-and of the Water of Sec. 19 Sales hand the old maps seess in No. 5 7305 Austrance No. 18985 Detected hand the owner in Address Note that on the permittee in Address Note that the permittee in Address Note that the permittee in Address Addres	Contin	ental-	State 7	erator Vell No	1	in NE	of NW pof Sec	c. 19		T 13-5	
Sinte land the Oil and gas lease in No. B 7305 Assignment No. 18395 Jacket land the other of gas lease in No. B 7305 Assignment No. 18395 Jacket land the owner in Address Address	32 E	Lease	r Mr IP Mr	C	aprock	Field		Lea		Cou	nty.
State hand the office to graduate in No. B 7305 putented hand the owner is of Lesses in	ell is E	360 en	ot courth of th	a North li	ne and 1	98 0 feet	work of the East	Fine of	ec. I	9	
Address Addr	State lan	nd the oil a	nd gas lease i	s N o	В 730	5 Assign	ment No	.8385			
### Address 1.0	patented	l land the	owner is				, А	ddress			
MINDER COMMERCED 19. 41. 19. 4	Governm	nent land t	he permittee	is			, A	ddress			,
reation above sea level at top of easing- feet. No request No request No request No remo OL SANDS OR ZONES 10. 3052 to 3059 TD No. 5 from 10. 8. from 10. 10. 8. from 10. 11. from 12. to 280 2. from 10. 12. to 280 2. from 10. 12. to 280 2. from 10. feet 10.	e Lessee	: is	 ∛∩¹	8	4	7 Deillin	a was complete	daress Jan	. 27.	19	48
THE PROOF SHEED IN THE RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE OF SHEED IN SHEED OF SHOOTING OR CHEMICAL TREATMENT SHEED SHEEL CRED OF SHOOTING OR CHEMICAL TREATMENT FLUGS AND ADAPTERS SHEEL CRED OF SHOOTING OR CHEMICAL TREATMENT FRECORD OR SHOOTING OR CHEMICAL TREATMENT	illing co	ommenced	master H	. L. W:	ilson Dr	illing (lompany, a	Address Mi	dlad,	Texas.	
Solution and the series of the	ovetion c	hove see 1	evel at top of	casing	4578	feet.					
OIL SANDS OR ZONES OIL SANDS OR ZONES No. 4, from 5056 to 3059 TD No. 5, from to No. 6, from N	ne inform	nation give	n is to be kep	t confident	ial until	No rec	uest	1	9		
DIPORTANT WATER SANDS clude data on rate of water inflow and clevation to which water rose in hole. 1. No. 5, from. DIPORTANT WATER SANDS clude data on rate of water inflow and clevation to which water rose in hole. 2. 20					OTT. S	SANDS OR 7	ONES				
Didde data on rate of water inflow and elevation to which water rose in hole. 12 to 280 feet. 13 to 280 feet. 14 to 280 feet. 15 to 280 feet. 16 to 280 feet. 18 to 280 feet. 19 to 280 feet. 20 to 19 to 19 to 280 feet. 20 to 10 sept. used to drill from 120' to 19 feet. 20 to 10 sept. used to drill from 120' to 19 feet. 20 to 6. 4 from 10 sept. 10 sept. 10 feet. 20 to 6. 4 from 10 feet. 20 feet to 30 feet. 21 to 6 from 10 from 10 feet. 22 to 70 feet to 10 feet. 23 to 70 feet. 24 to 6 freed. 25 to 70 feet. 26 to 70 feet. 27 to 70 feet. 28 to 70 feet. 29 to 70 feet. 20 feet.	3052 to 3054 Ne. 4, fromto										
CASING RECORD MUDDING AND CEMENTING BECORD MUDDING AND CEMENTING BECORD MUDDING AND CEMENTING BECORD MUDDING AND CEMENTING BECORD MUDDING AND CEMENTING WATER SET OF CEMENT SIZE SIZE SIZE SIZE SIZE SIZE SIZE SIZE	No. 2 from 5056 to 3069 TD			069 ID	No. 5	to					
Clude data on rate of water inflow and elevation to which water rose in hole. 12 to 280 1. from 12 to 280 2. from Rectary tools were used to drill from 120' to Leave 1500 150 150 150 150 150 150 150 150 15	o. 3, fror	m		to		No. 6	, from	•••••	ТО	••••••••	
12 to 280 feet 120 fe											
Solary tools were used to drill from to to and no water tests were made in stove said. 3. from to to feet. 3. from the field of feet. 4. from the field of from the feet of feet. 4. from the field of from the feet of feet to feet to feet. 4. from the field of free from feet to feet to feet. 4. from the free feet to feet to feet. 4. from the free feet to feet to feet. 4. from the free feet to feet to feet. 4. from the free feet. 4. from the free feet. 4. from the free feet. 4. from from free feet. 4. from the free feet. 5. freet. 5. freet. 5. freet. 5. freet. 6.			•	1 0	20	20		t	302	28	•
CASING RECORD SIZE PER FOOT THERADS MAKE AMOUNT SIND OF COT A THLES PER FOOT TEB NOCH THE NOW TO PURPOSE THE NOW TO THE NOW TO PURPOSE THE NOW THE NOW TO THE NOW THE NOW TO THE NOW THE NOW TO THE NOW THE		n									
CASING RECORD CASING CASING WIRERE SET OF CASING METHODS USED MUD GRAVITY AMOUNT OF MUD USED CASING CASING WIRERE SET OF CASING METHODS USED MUD GRAVITY AMOUNT OF MUD USED CASING CASING WIRERE SET OF CASING METHODS USED MUD GRAVITY AMOUNT OF MUD USED CASING PLANS AND ADAPTERS Length Depth Set CASING PUBL—Material Size CASING OF SHOOTING OR CHEMICAL TREATMENT CASING CHEMICAL USED CASING CASING FROM ITERATED DEPTH CLEANED OUT AND ADAPTED CASING CASING CASING FROM ITERATED DEPTH CLEANED OUT AND ADAPTED CASING CASING CASING FROM ITERATED DEPTH CLEANED OUT AND ADAPTED CASING CASING FROM ITERATED CASING CASING CASING FROM ITERATED CASING CASING CASING FROM ITERATED CASING CASING CASING CASING CASING CASING CASING FROM ITERATED CASING). 2, Iroi o 3 froi	m	nd no w	ater t	to	ere made	in above	sanu•		·	
SIZE VERYOUT THERADE MAKE AMOUNT RIDGY OF STRAME PERFORMAND PERFORMAND TO PURPOSE SOLUTION OF STRAME PROMISE STRAME TO STRAME	o. 4, fro	m			to		fee	:t		·	
NUDDING AND CEMENTING RECORD Note	·										
MUDDING AND CEMENTING RECORD Mark			munua ng	<u> </u>		KIND OF	CUT & FILLED	PERF	RATED	PURPOSE	===
### STATE OF STATE OF WHERE SET OF CAMENT OF CAMENT OF CASHON OF THE CHANGE OF STATE OF CASHON O		PER FOOT	PER INCH	MAKE	AMOUNT	SHOE	FROM	FROM	то	1011 004	
MUDDING AND CEMENTING RECORD No. Size	10 3	/4 "OD 32-75	1				Guide-Flo	pat.			
MUDDING AND CEMENTING RECORD MUD GRAVITY AMOURT OF MUD URED	5/8" 3/4 " 0	D 15#							to 30	0 69') Perf	orat
METHODS USED SIZE OF CASING WHERE SET OF CEMENT METHODS USED MUD ORAVITY AMOUNT OF MUD USED 3/4 " 6 5/3 3022" 600 " " " " " " FLUGS AND ADAPTERS Length Depth Set Size BECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OR THEATED DEPTH CLEANED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3063 3069 Whith Set Squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS defill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Colory tools were used from 120 feet to 120 feet, and from 3028 feet to 3069 TD feet able tools were used from 0 feet to 120 feet, and from 3028 feet to 3069 TD feet more of the first 24 hours was 72 barrels of fluid of which 100 % was oil; standing from test took pressure, lbs. per sq. in. No test STEM CALLY OF STEM CALLY SAND SPECIAL TESTS Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST GALLON SP	,										
METHODS USED SIZE OF CASING WHERE SET OF CEMENT METHODS USED MUD ORAVITY AMOUNT OF MUD USED 3/4 " 6 5/3 3022" 600 " " " " " " FLUGS AND ADAPTERS Length Depth Set Size BECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OR THEATED DEPTH CLEANED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3063 3069 Whith Set Squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS defill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Colory tools were used from 120 feet to 120 feet, and from 3028 feet to 3069 TD feet able tools were used from 0 feet to 120 feet, and from 3028 feet to 3069 TD feet more of the first 24 hours was 72 barrels of fluid of which 100 % was oil; standing from test took pressure, lbs. per sq. in. No test STEM CALLY OF STEM CALLY SAND SPECIAL TESTS Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test took pressure, lbs. per sq. in. No test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST Gallons gasoline per 1,000 cu. ft. of gas 100 test STEM CALLY SAND SPECIAL TEST GALLON SP							-				
METHODS USED AMOUNT OF MUD USED MUD GRAVITY AMOUNT OF MUD USED PLUGS AND ADAPTERS Length Depth Set Size BECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR GRAVITY MITTO GlyC. MITTO GlyC. MITTO GlyC. MOD GRAVITY MOD GRAVITY MOD GRAVITY DATE OR TREATED DEPTH GHOW OF TREATED DEPTH CLEANED OUT OR TREATED DEPTH CLEANED OUT MITTO GlyC. MOD GRAVITY DATE OR TREATED DEPTH CLEANED OUT OR TREATED DEPTH CLEANED OUT TO SEE TO SE TO SE TO SE											
No. SACKS OF CASING WHERE SET NO. SACKS OF CEMENT METHODS USED MUD GRAVITY AMOUNT OF MUD USED											
PLUGS AND ADAPTERS Teaving plug—Material				M	JDDING A	ND CEMENT	TING RECORD				
PLUGS AND ADAPTERS Reaving plug—Material Length Depth Set RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OF TREATED DEPTH SHOT OF TREATED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment Shot split 6 5/8" casing from 1267" to 1278! Thic was squarezed with 100 sex. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED ROCALL STEM AND SPECIAL TESTS Of the complete of the complet	IZE OF	SIZE OF CASING	WHERE SET	NO. SACI	KS ME	THODS USED	MUD GR.	AVITY	AMOU	NT OF MUD USE	D
PLUGS AND ADAPTERS teaving plug—Material Length Depth Set RECORD OF SHOOTING OR CHEMICAL TREATMENT Size SHELL USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE OR THEATED DEPTH CLEANED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment Shot split 6 5/8" casing from 1267' to 1278' This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED ROTATY tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 3069 TD fee cable tools were used from 0 feet to 120 feet, and from 3028 feet to 3069 TD fee production of the first 24 hours was 72 barrels of fluid of which 100 % was oil: TOOLS USED PRODUCTION 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil: Tools used Form 100 feet of 120 feet of	5 10 3/4" 291 150 Halliburton Well Cementing Co.										
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE DEPTH SHOT OR THEATED DEPTH CLEANED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment. Shot split 6 5/8" casing from 1267' to 1278' This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED ROTOLS USED ROTOLS USED ROTOLS USED ROTOLS USED ROTOLS WERE USED from 0 feet to 3028 feet, and from 3028 feet to 3069 TD feet PRODUCTION PROPUCTION Lay 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil: 9 semulsion; % water; and 8 sediment. Gravity, Be. 36 ROCK pressure, lbs. per sq. in	3/4	6 5/8	30221	60	0	- 11	- 18		Ħ		
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OR THEATED DEPTH CLEANED OUT Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment. Shot split 6 5/8" casing from 1267' to 1278' This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED TOOLS USED Actory tools were used from 120 feet to 3028 feet, and from 3028 feet to 3069 TD feet Cable tools were used from 0 feet to 120 feet, and from 3028 feet to 3069 TD feet PRODUCTION PRODUCTION PROPUCTION											
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEPTH CLEANED OUT OR TREATED OR TREATED DEPTH SHOT OR TREATED	!_		<u> </u>	-							
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEPTH CLEANED OUT OR TREATED OR TREATED DEPTH SHOT OR TREATED	l eaving	plug—Mate	erial			Lengt	h	D e	pth Set		·
SIZE SHELL USED CHEMICAL USED QUANTITY DATE OF TREATED DEPTH CLEANED OUT OF THE SHOT OF TH	dapters	— Materia	1		•••••		Size			•••••	·
Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment. Shot split 6 5/8" casing from 1267' to 1278' This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to producing. PRODUCTION PRODUCTION PRODUCTION PRODUCTION Production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; semulsion; % water; and % sediment. Gravity, Be 36 no test Rock pressure, lbs. per sq. in No test			:	RECORD	OF SHOOT	ring or ce	IEMICAL TREA	ATMENT			
Nitro Glyc. 30 qt. 3-5-48 3054-3069 3069 Results of shooting or chemical treatment. Shot split 6 5/8" casing from 1267 to 1278. This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 0 feet to 3028 feet, and from 5028 feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to producing. May 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 9 semilation; % water; and 72 barrels of fluid of which 100 % was oil; 9 semilation; % water; and 72 sediment. Gravity, Be. 36 no test 1200 feet to 1200 f	917F	SHELL	USED	EXPLOSIV	E OR	QUANTITY	DATE	DEPTH OR TRE	SHOT ATED 1	DEPTH CLEANED	OUT
Results of shooting or chemical treatment. Shot split 6 5/8" casing from 1267! to 1278! This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 3069 TD feet PRODUCTION Put to producing May 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 20 mulsion; % water; and % sediment. Gravity, Be 36 no test Rock pressure, lbs. per sq. in. No test		- BITELE				30 qt	3-5-48	3054·	-3069	3069	
This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS for drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED totary tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 120 feet, and from 3028 feet to 3069 TD feet to 120 feet t											
This was squeezed with 100 sax. cement on March 15, 1948 and complete shutoff resulted. RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to producing May 3, 19 48 Pumping PRODUCTION PRODUCTION Production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 19 48 pumping semulsion; % water; and % sediment. Gravity, Be 36 mo test Rock pressure, lbs. per sq. in No test Rock pressure, lbs. per sq. in No test						7	<u> </u>	ina fas	m 1067	11 +0 1279	
RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to production PRODUCTION PRODUCTION PRODUCTION PROPULTION Put to production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; Semulsion; % water; and % sediment. Gravity, Be 36 If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas. Rock pressure, lbs. per sq. in No test	Results o	f shooting	or chemical	treatment	Shot	split 6	b/8" cas:	ing iro	1948 s	ona comple	ii
RECORD OF DRILL-STEM AND SPECIAL TESTS f drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 5028 feet to 3028 feet to 3028 feet to 5028 feet to	Thi	is was	squeeze	d with	TOO sa	x. cemer	it on Marc	ون ۱ الز	1340 6	ma comore	
TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 3069 TD feet to producing May 3, 19 48 Pumping Put to production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; menulsion; % water; and % sediment. Gravity, Be 36 If gas well, cu. ft. per 24 hours. No test FAMILIANT OFFES.	8110				n of nri	TI_STEM A	ND SPECIAL T	ESTS		•••••	•••••••
TOOLS USED Rotary tools were used from 120 feet to 3028 feet, and from feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to producing May 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; memulsion; water; and sediment. Gravity, Be 36 If gas well, cu. ft. per 24 hours Mo test Rock pressure, lbs. per sq. in No test	,e .ji]] at	om or other	m enerial tests						neet and a	attach hereto.	
Rotary tools were used from 120 feet to 3028 feet, and from feet to 3069 TD feet to 120 feet, and from 3028 feet to 3069 TD feet to production PRODUCTION Put to production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; Pumplicy Be 36 Rock pressure, lbs. per sq. in No test FMELONEES	i arm-so	em or oure	i special tesa.	, 01 40 1340							
PRODUCTION Put to producing May 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; emulsion; % water; and % sediment. Gravity, Be 36 If gas well, cu. ft. per 24 hours Mo test Rock pressure, lbs. per sq. in No test FMPIONEES	Potery to	ols were II	sed from	120	feet to	3028	foot and from		feet	to	feet
PRODUCTION Put to producing May 3, 19 48 Pumping The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 99 water; and 90 test If gas well, cu. ft. per 24 hours Mo test Rock pressure, lbs. per sq. in No test Final Cypers Final Cypers	Cable too	ols were us	ed from	0	feet to	.20	feet, and from	30.28	feet	to 3069 TL	feet
The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 25 barrels of fluid of which 100 % was oil; 26 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 28 barrels of fluid of wh						PRODUCTIO	ON				
The production of the first 24 hours was 72 barrels of fluid of which 100 % was oil; 25 barrels of fluid of which 100 % was oil; 26 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 27 barrels of fluid of which 100 % was oil; 28 barrels of fluid of wh	out to pr	oducing	May	3,		1948	Pumping	7.0	0		
If gas well, cu. ft. per 24 hours	The prod	luction of t	he first 24 h	ours was	72	barre	els of fluid of wh	nichLU	∪% w	as oil;	%
Rock pressure, lbs. per sq. in	mulsion	;	% water;	and No te	% s s t	ediment. Gra	avity, Be			no test	;
EMDI OVEES							ons gasoline per	1,000 cu. ft	o oi gas	•••••	
EMPLOXEES	Rock pre	ssure, lbs.	per sq. in		res t		7.C				
J. H. Simmons (Rotary) Driller H. L. Wilson Cable tools Drille	J.	H. Si	mmons (Rotary)	EMPLOXEI Driller	ss H. L. Wil	son Ca	ble t	ools	Driller
R. V. Wade "Driller Fred F. Johnson " Driller Driller Pred F. Johnson Driller Driller Driller Pred F. Johnson Driller	R.	V. Wa	de	11	,	Driller	Fred F. J	ohnson			
FORMATION RECORD ON OTHER SIDE				•	-)E		, ,	
Thereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done of	l haust-	PW00* 0* 0*	ffirm that th						of the wel	l and all work do	one on

5th

., 48

Subscribed and sworn to before me this.....

Maw

FORMATION RECORD

FORMATION RECORD									
FROM	то	THICKNESS IN FEET	FORMATION						
0 12 260 1500 1580 1700 1840 2400 2410 2765 3010 3020 3040 3050 3052 3054 3056	12 260 1500 1580 1700 1840 2410 2765 3010 3050 3052 3054 3056 3069	80 120 140 560 10 355 245 10 80 10 2	Rock and caliche Sand Red Bed Anhydrite Salt Anhyd. Salt & Anhyd. Potash & Salt. Ankyd. Anhyd. & Red Bed. Anhyd. Red Sam Rock Anhyd. Anhyd. Sand with trace of oil. Anhyd. Very hard. Oil Sand.						