		Form C-103
NO. OF COPIES RECEIVED		Supersedes Old C-102 and C-103
DISTRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
SANTA FE	/	
FILE	ĬĹŮ S	a. Indicate Type of Lease
U.S.G.S.		State X Fee
LAND OFFICE		5. State Oil & Gas Lease No
OPERATOR		
(DO NOT USE THIS F	SUNDRY NOTICES AND REPORTS ON WELLS ORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. "Application for Permit" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
l. OIL GAS	Dry hole held for water source	
WELL WE		8. Farm or Lease Name
2. Name of Operator	Water Source Lease	
Great Western	9. Well No.	
3. Address of Operator	70701	1
P. O. Box 165	9 Midland, Texas 79701	10. Field and Pool, or Wildcat
4. Location of Well	North 660	Wildcat
UNIT LETTERD	660 FEET FROM THE NORTH LINE AND 660 FEET FROM	
ONTI EZITE	27 13-S 32-E NMPM.	
THE West	LINE, SECTION 27 TOWNSHIP 13-S RANGE 32-E NMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
		Lea
VIIIIIIII	4340 DF	or Data
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Other Subsequent	er Data
пот	ICE OF INTENTION TO:	REPORT OF:
		ALTERING CASING
PERFORM REMEDIAL WORK	PLUG AND ABANDON X REMEDIAL WORK	<u>~</u>
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	·
PULL OR ALTER CASING	OTHER	
OTHER		estimated date of starting any propose
17 Describe Proposed or	Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of ourself with the
work) SEE RULE 110	3.	
m :11 haa	13-3/8" casing set at 415' and 9-5/8" casing set at 3,8	60' (cement
This Well has	13-3/8" casing set at 415' and 9-5/8" casing set at 5,0 A 5-1/2" liner was set from 3700' to 12,374' and cement	ed with /00
circulated).	cement outside 5-1/2" liner is 8,005' by temperature su	rvey. There
sacks; top of	ia. open hole from 12,374' to 12,662'. It is proposed to	o set cast
is a 6-3/4" d	ia. open hole from 12,374' to 12,662'. It is proposed to lugs at 12,350' and at 3,750' and place 5 sacks cement of	n top of each
iron bridge p	lugs at 12,550 and at the surface.	
plug. A 25 s	ack plug will be placed at the surface.	

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

Chief Engineer

DATE February 2, 1970

APPROVED BY

CONDITIONS OF APPROVAL, IF KNY:

			1
			1
			1
•			
		•	
			:
			8 8 9 9 9 9
			1