

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) PLUGGING BACK	XX

November 6, 1952
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation, Lea State "AT"
(Company or Operator) (Lease)Gardner Brothers Drilling Company, Well No. 1 in the SW 1/4 NW 1/4 of Sec. 21
(Contractor)

T. 14-S, R. 32-E, NMPM, Undesignated Pool, Lea County.

The Dates of this work were as follows: October 31 - November 5, 1952

Notice of intention to do the work ~~xxxx~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)and approval of the proposed plan ~~xxxx~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 13,465' Went in hole to 13,135'. Plug back with heavy mud from 13,465' to 13,135'. Spotted 69 sacks Trinity Inferno cement from 13,135' to 12,985', displaced with 82 bbls mud. Heavy mud from 12,985' to 10,025' and 93 sacks of Trinity Inferno cement with 10 bbls water ahead cement from 10,025' to 9825'. Displaced cement thru 2-3/8" tubing with 38 bbls mud, complete by HOWCO at 3:00 AM 10-31-52. Pulled tubing out of hole. Went in hole w/8-3/4" bit in 12 hrs found soft cement top at 9869'. Drilled off to 9879', hard cement. Spotted plug at 9879' w/30 sacks Trinity Inferno cement with 10 bbls lime water pumped ahead of cement. Displaced w/38 bbls of mud. WOC 12 hrs went in hole w/8-3/4" bit, found top cement at 9825'. Drilled cement off from 9825' to 9850'. Job completed 1:01 AM November 2, 1952

Witnessed by J. E. Sneed, Gulf Oil Corporation, Drilling Foreman
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: _____

Position: Area Prod. Supt.

Representing: Gulf Oil Corporation

Address: Box 2167, Hobbs, New Mexico

Engineer District

NOV 12 1952

(Title)

(Date)