NEW-MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is

	will be given the approval, with any modifications the plan submitted. The plan as approval should be see additional instructions in the Roses of HOBRS.	lations of
	otice by checking below:	FFICE
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		-
Midland, Texas	April 2, 1952 Date	·····
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico Gentlemen:		
The Taxas Company St. of NM. "AU"  Company or Operator  Lease	escribed below at the	NW 1/4 NW 1/
of Sec		
Lea County.		
FULL DETAILS OF PR	OPOSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE RULES	S AND REGULATIONS OF THE COMMISSION	
TD: 13500-De	olomite	
8' 13 3/8" casing set at 362' with 57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' wit	400 sacks cement. Cement circ 2400 sacks cement. th 200 sacks cement.	culated.
8' 13 3/8" casing set at 362' with 57' 8 5/8" casing set at 3970 with 48' 5 1/2" casing set at 9860' with is well has been drilled to a total or Gas in Commercial quantities. d plug well in the following manner	2400 sacks cement. th 200 sacks cement. l depth of 13500' without enco We the <b>refo</b> re desire to abandon	untering
57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' with is well has been drilled to a total or Gas in Commercial quantities. d plug well in the following manner ing Heavy Mud between plugs, spot 160'; 25 sacks 12335-12405'; 20 sacks 9567' - 9526'; 30 sacks 446' ll. same); 30 sacks 3895'-3935';	2400 sacks cement. th 200 sacks cement.  l depth of 13500' without encounce the refore desire to abandon r.  the following cement plugs; 25 cks 11215'-11175'; 30 sacks 9885'-4365'; (Cut off 5 1/2" casin	untering n salvage sacks 13100 85'-9835'; ng at 4465'
57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' with is well has been drilled to a total or Gas in Commercial quantities. d plug well in the following manner ing Heavy Mud between plugs, spot 160'; 25 sacks 12335-12405'; 20 sacks 9567' - 9526'; 30 sacks 446' ll. same); 30 sacks 3895'-3935';	2400 sacks cement. th 200 sacks cement.  l depth of 13500' without encounce the refore desire to abandon r.  the following cement plugs; 25 cks 11215'-11175'; 30 sacks 9885'-4365'; (Cut off 5 1/2" casin (Cut off 8 5/8" casing at 600 a	untering n salvage sacks 13100 85'-9835'; ng at 4465'
57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' with is well has been drilled to a total or Gas in Commercial quantities. d plug well in the following mannering Heavy Mud between plugs, spot 160'; 25 sacks 12335-12405'; 20 sacks 9567' - 9526'; 30 sacks 446' ll. same); 30 sacks 3895'-3935'; me) 5 sacks top 13 3/8" casing.	2400 sacks cement. th 200 sacks cement.  l depth of 13500' without encounce the refore desire to abandon results.  the following cement plugs; 25 cks 11215'-11175'; 30 sacks 9885'-4365'; (Cut off 5 1/2" casing (Cut off 8 5/8" casing at 600 and the Texas Company	untering n salvage sacks 13100 85'-9835'; ng at 4465' and pull
57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' with is well has been drilled to a total or Gas in Commercial quantities. d plug well in the following mannering Heavy Mud between plugs, spot 160'; 25 sacks 12335-12405'; 20 sacks 9567' - 9526'; 30 sacks 446' ll. same); 30 sacks 3895'-3935'; me) 5 sacks top 13 3/8" casing.	2400 sacks cement.  th 200 sacks cement.  l depth of 13500' without encounce.  We therefore desire to abandour.  the following cement plugs; 25 cks 11215'-11175'; 30 sacks 9885'-4365'; (Cut off 5 1/2" casing (Cut off 8 5/8" casing at 600 at	untering n salvage sacks 13100 85'-9835'; ng at 4465' and pull
57' 8 5/8" casing set at 3970 with 48' 5 1/2 " casing set at 9860' with 1s well has been drilled to a total or Gas in Commercial quantities. d plug well in the following manner ing Heavy Mud between plugs, spot 160'; 25 sacks 12335-12405'; 20 sacks 9567' - 9526'; 30 sacks 446' ll same); 30 sacks 3895'-3935'; me) 5 sacks top 13 3/8" casing.  Approved sacks 13 3/8" casing.	2400 sacks cement.  th 200 sacks cement.  l depth of 13500' without encounce we therefore desire to abandon results.  the following cement plugs; 25 cks 11215'-11175'; 30 sacks 9885'-4365'; (Gut off 5 1/2" casing (Gut off 8 5/8" casing at 600 at 600 at 600 seed communications regarding with the communications r	untering n salvage sacks 13100 85'-9835'; ng at 4465' and pull