

W MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an

	indicate nature	or report	t by checking be	low.		
REPORT ON BEGINNING	G DRILLING	-	REPORT ON	REPAIRIN	G WELL	
REPORT ON RESULT OF CHEMICAL TREATM		REPORT ON PULLING OR OTHERWISE ALTERING CASING				
REPORT ON RESULT OF SHUT-OFF	TEST OF CASING		REPORT ON	DEEPENI	G WELL	
REPORT ON RESULT OF	PLUGGING OF WELL	X				
	February 29,	1952,)	Midlan	d, Texas	
			Date		Place	e
Following is a report on the	e work done and the results ob	tained ur	ider the heading r	noted above a	t the	
	ny State of I					
Comp	sany or Operator	,	Lease	Well No)	in the
	oany or Operator of Sec. 31	······································	T 14-S	, R	32-E	, N. M. P. M.,
ildcat	Lea Pool					County
						County.
	e as follows: See Below					
Notice of intention to do th	ne work was (was not) submit	ted on Fo	orm C-102 on	reorua	ry 13	19
	ed plan was (*********** obtained					
	ETAILED ACCOUNT OF W				NED	
D	TD: 13727 PI			LIS ODIAL	NED	
	10. 17/2/ 11	J. 44,	O -DIME			
2' 13 3/8" cas 8' 8 5/8" cas	ing set at 336' ving set at 3920'	with 3 with	350 sacks 25 00 s ack	cement, s cemen	Cement ci	irculate cir cu la
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 336' ving set at 3920' tween cement plug; 15 sacks 3944-2 in hole; bottom sack plug in top	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas	ing set at 3920'	with	2500 sack	s cemen	t. Cement	circula
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15	ing set at 3920' tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with	2500 sack cotted the cottom 8 5 /8" casing /8" casing	s cemen	t. Cement ing cement ing at 392 , all 8 5/	circula plugs: 0, all /8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15	ing set at 3920' tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with	2500 sack	s cemen	t. Cement ing cement ing at 392 , all 8 5/	circula
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15	ing set at 3920' tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5 /8" casing /8" casing	follow /8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula c plugs: 20, all /8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15 Witnessed by	ing set at 3920' tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5 /8" casing /8" casing	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula c plugs: 20, all /8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15 Witnessed by	ing set at 3920' tween cement plug; 15 sacks 3944-7 in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5/8" casing Company	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula c plugs: 20, all /8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15 Witnessed by	ing set at 3920' tween cement plug; 15 sacks 3944-7 in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5 8" casing Company Company I hereby swear of is true and correct Name	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula c plugs: 20, all /8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15 Witnessed by	tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5 8" casing 8" casing Company. I hereby swear of is true and correct Name Ass't	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula plugs: 0, all 8" casi
ng heavy mud be sacks 4450-4300 (/8" casing left tin hole.) 15	tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack otted the ottom 8 5 /8" casing /8" casing Company I hereby swear of is true and correct Name Position Ass't	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula plugs: 0, all 8" casi
8' 8 5/8" cas ng heavy mud be sacks 4450-4300 /8" casing left t in hole.) 15 Witnessed by	tween cement plug; 15 sacks 3944-; in hole; bottom sack plug in top	with gs, sp 3899(1 13 3/	2500 sack cotted the cottom 8 5 8" casing Company Company I hereby swear of is true and correct Name	follow/8" cas at 336	t. Cement ing cement ing at 392 , all 8 5/	circula c plugs: 20, all /8" casi