

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC - 060581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. T. Caudle

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Bagley

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T-12S, R-33E

12. COUNTY OR PARISH

Lee

13. STATE
New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Amerada Petroleum Corporation

3. ADDRESS OF OPERATOR

P. O. Box 668 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 660' FNL of Sec. 10

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4257' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pulled tubing and flow valves. Reran tubing & squeezed 5-1/2" casing perfs. 9316' to 9326' with 50 sacks cement. Halliburton temp. blocked 5-1/2" casing perfs. 9000' to 9066' with 1000 gals. Halliburton Temblock. Squeezed 5-1/2" casing perfs. 8664' to 8714' with 225 sacks cement. Drilled out cement. Ran Lane Wells Gamma Ray Neutron log from 8650' to 9435'. Perforated 5-1/2" casing from 9264' to 9269', 9284' to 9290', 9356' to 9360', 9378' to 9384' & 9412' to 9422' with 2 shots per foot. Acidized perfs. 9412' to 9422' with 1000 gals. 15% NE acid. Stab tested. Nonproductive. Acidized perfs. 9356' to 9384' with 1000 gals. 15% NE acid. Stab tested. Nonproductive. Acidized perfs. 9264' to 9290' with 1000 gals. 15% NE acid. Stab tested. Nonproductive. Ran Baker Model "N" cast iron bridge plug set at 9220'. Reran tubing with flow valves. Resumed flowing by gas lift from perfs. 9000' to 9066' for observation purposes.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Superintendent

DATE 4-11-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 19 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

APR 10 1964
MAIL ROOM
U.S. GOVERNMENT PRINTING OFFICE