

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

OCT - 3 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	<b>X</b>

September 29, 1950

Museum, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amarada Petroleum Corporation

State of N. M.

Well No. 1

in the

Company or Operator

Lease

C/NE/4 NE/4

of Sec. 11

T. 12-S

R. 33-E

N. M. P. M.

Ragley-Siluro Devonian

Field

Lea

County.

The dates of this work were as follows: September 29, 1950

Notice of intention to do the work was submitted on Form C-102 on September 28, 1950

and approval of the proposed plan was obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3903' - Total Depth - Line. Ran Schlumberger Electrical & Gamma Ray Surveys. Ran 8 1/2" Dia. 36' & 40' Dia. 32', 4-5/8" O.D. Grade J-55 S.S. Casing, 8-Dia. Thd., set at 3889' and cemented with 1000 sacks Regular cement, mixed with 3% Jell, and 450 sacks Regular cement and 50 sacks MI-early cement - Total of 1500 sacks. Plug to 3824' at 1:47 A.M., 9-29-50. Maximum pump pressure 7904.

Witnessed by D. F. Purse

Amarada Petroleum Corporation

Foreman

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

29th day of September, 1950

Name D. W. Topp

Position Assistant District Superintendent

Representing Amarada Petroleum Corporation

Company or Operator

My commission expires 10-24-53

Address Drawer B, Museum, New Mexico

Remarks:

PROVED  
OCT - 3 1950

Reg. Yanhoush  
Oil & Gas Inspector

Title