

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |  |  |   |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |  | REPORT ON REPAIRING WELL                       |   |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |  | REPORT ON PULLING OR OTHERWISE ALTERING CASING |   |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |  | REPORT ON DEEPENING WELL                       |   |
| REPORT ON RESULT OF PLUGGING OF WELL                       |  | REPORT ON SETTING CASING                       | X |

February 12, 1951

Mammoth, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation L. M. Chambers Well No. 2 in the  
Company or Operator Lease

C/NE/A NW/4 of Sec. 11, T. 12-S, R. 33-E, N. M. P. M.,

Bagley-Siluro/Devonian Field Lee County.

The dates of this work were as follows: February 10, 1951

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on February 10, 1951

and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

312' - Total Depth - Red Bed. Ran 10-3/4" O.D., 28.25#, 40.5# & 40#; Slip Joint, 8-Md. Tpd. & 8-V-Tpd.; Spiral Weld, S.S., & L.W.; New & SH Casing, set at 306' and cemented with 175 sacks Regular & 50 sacks Inocer Cement. Plug to 290' at 2:00 P.M., 2-10-51. Maximum pump pressure 225#. Cement circulated.

Witnessed by G. E. Telge Amerada Petroleum Corporation Foreman  
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

12th day of February, 1951

Name Don Tepp

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires 10-11-54

Address Drawer D, Mammoth, New Mexico

Remarks:

APPROVED

Date FEB 13 1951

Roy Yorkrough  
Name  
Oil & Gas Inspector  
Title

