


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

April 10, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation J. E. Simmons et al Well No. 1 in the

C/NW/4 NW/4 Company or Operator 11 Lease 12-8 of Sec. 11, T. 12-S, R. 33-E, N. M. P. M., Wildcat Field, Lea County.

The dates of this work were as follows:

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on April 6, 1950 and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,046' Total Depth - Lime, 9460' Plugged Back Depth. Ran Schlumberger & Lane-Wells Surveys. Ran 223 Joints, of 5-1/2" O.D. 17#, 8-Rd. Thd., Range 3, S. S. New Casing - Set at 9450'. 10 - 5 1/2" Baker Centralizers from 9435' to 8990' and 20 - 5 1/2" Weatherford Wall Scratchers, spaced 15' apart, from 9435' to 9295' and from 9080' to 8990'. Circulated one hour and cemented with 600 sacks of Trinity Sls-Set cement, mixed 3% Jell and 1/4# of Flow Seal per sack. Pumped plug to 9365' at 4:15 P.M., 4-8-50. Maximum pump pressure 2200#.

Witnessed by <u>C. E. Telge</u>	<u>Amerada Petroleum Corporation</u>	<u>Farm Boss</u>
Name	Company	Title
Subscribed and sworn before me this <u>10th</u> day of <u>April</u> 19 <u>50</u>		
I hereby swear or affirm that the information given above is true and correct.		
Name <u>Don Tepp</u>		
Position <u>Assistant District Superintendent</u>		
Representing <u>Amerada Petroleum Corporation</u>		
Company or Operator		
Address <u>Drawer D, Monument, New Mexico</u>		
My commission expires <u>10-24-53</u>		

Remarks: As Witnessed
Don Tepp
10-24-53

Don Tepp
Name
Assistant District Superintendent
Title

Handwritten text at the top of the page, possibly a title or header.

Handwritten text in the upper middle section of the page.

Handwritten text in the middle section of the page.

Handwritten text in the lower middle section of the page.

Handwritten text at the bottom of the page, including a signature and date.