

ORIGINAL
IMMEDIATE

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED
JUL 14 1951
OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications suggested, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Monument, New Mexico
Place

July 12, 1951
Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Amorata Petroleum Corporation Charles L. Turner Well No. 1 in Q/EE/4 SW/4
Company or Operator Lease
of Sec. 11, T. 12-S, R. 33-E, N. M. P. M. Bagley-Silvers/Denverian Field.
La County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

11,115' - Total Depth - Line & Chart. Finished drilling 7-7/8" hole at 10:00 A.M., 7-11-51. No oil or gas shows of consequence were encountered. It is our intention to plug and abandon this well, after running Schlumberger's Gamma Ray & Electrical Surveys. We propose to plug the well as follows: 35 sacks of cement from total depth to approx. 18700', 35 sacks of cement from 1810' to 18670', 35 sacks of cement from 18000' to 18800', 25 sacks of cement from 18300' to 18490'. Cut off 8-5/8" casing at approximately 19300' & recover same. 35 sacks of cement from 115' to 270' into 13-3/8" O.D. Casing, then dump 10 sacks of cement in top of the 13-3/8" surface casing. Set a piece of 4" Line Pipe, cemented in center of surface casing, extending 5' above surface of the ground. Heavy mud between all above cement plugs.

Approved JUL 16 1951, 19
except at follows:

Amorata Petroleum Corporation
Company or Operator

By [Signature]

Position Assistant District Superintendent
Send communications regarding well to

Name Amorata Petroleum Corporation

Address Dresser B, Monument, New Mexico

OIL CONSERVATION COMMISSION

By Noy Yurkewich
Title Oil & Gas Inspector

