
## Form C-100 LICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico





Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERA- TIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO Gentlemen:	January 19, 1950 Monument, New Mexico Date Place
Following is a report on the work done and the resultance and Petroleum Corporation	Its obtained under the heading noted above at the
Company or Operator	Lease
C/SE/4 5W/4 of Sec. 23	, T12-S, R33-E, N. M. P. M.,
Wildcat Field,	Lea County.
The dates of this work were as follows: Januar	y 18, 1950
Notice of intention to do the work was	submitted on Form C-102 on January 16, 19 50
DEINIED ACCOUNT OF	WORK DONE AND RESILTS ORTAINED
3870' - Total Depth - Lime. Ran bit casing with 1500# for 1/2 ho	work done and results obtained  and found top of cement plug at 3795. Tested  ur - Satisfactory. Drilled out cement plug and  1/2 hour - satisfactory. Started drilling 7-3/8
3870' - Total Depth - Lime. Ran bit casing with 1500# for 1/2 ho tested casing with 1500# for hole at 9:45 PM. 1-18-50.	and found top of cement plug at 3795. Tested ur - Satisfactory. Drilled out cement plug and
3870' - Total Depth - Lime. Ran bit casing with 1500# for 1/2 ho tested casing with 1500# for hole at 9:45 PM. 1-18-50.	and found top of cement plug at 3795. Tested ur - Satisfactory. Drilled out cement plug and 1/2 hour - satisfactory. Started drilling 7-3/8
3870' - Total Depth - Lime. Ran bit casing with 1500# for 1/2 ho tested casing with 1500# for hole at 9:45 PM. 1-18-50.  Witnessed by C.E. Telge Amerada Pet	and found top of cement plug at 3795. Tested ur - Satisfactory. Drilled out cement plug and 1/2 hour - satisfactory. Started drilling 7-3/8.  Toleum Corporation Farm Boss  Company Title  I hereby swear or affirm that the information given above is true and correct.

The state of the s Say Mark St. Jak