

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	<b>X</b>
NOTICE OF INTENTION TO DEEPEN WELL			

Monument, New Mexico July 26, 1950  
Place Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the  
Amerada Petroleum Corporation State BT "F" Well No. 1 in G/SE/4 NW/4  
Company or Operator Lease  
of Sec. 23, T. 12-S, R. 33-E, N. M. P. M., Hightower Field.  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

11,185' - Total Depth - Line. Finished drilling 7-3/8" hole at 7:30 P.M., 7-24-50. No oil or gas seeps of consequence were encountered. It is our intention to plug and abandon this well, after running Schlumberger's Electrical & Gamma Ray Surveys and Schlumberger's Dipmeter Survey, as follows: Spot 35 sacks of cement from total depth to approximately 11055', heavy mud from 11055' to 8753', spot 35 sacks of cement at 8753' to approximately 8623', heavy mud from 8623' to 3950', spot 35 sacks of cement at 3950' to approximately 3850', (8-5/8" casing is set at 3900' and it is intended to have 50' of cement in the bottom of the 8-5/8" casing & 50' below the casing) spot 25 sacks of cement at 1550' and pull up to 1450' and circulate out. Shoot off 8-5/8" casing at approx. 1280' & recover same. Heavy mud from 1450' to 315' at which depth 35 sacks of cement will be dumped, then dump 10 sacks of cement in top of surface casing. Set piece of 4" Line Pipe, cemented in center of surface casing, 5' above surface of ground.

Approved AUG - 1 1950, 19\_\_\_\_  
except as follows:

Amerada Petroleum Corporation  
Company or Operator  
By [Signature]  
Position Assistant District Superintendent  
Send communications regarding well to  
Name Amerada Petroleum Corporation  
Address Drawer D, Monument, New Mexico

OIL CONSERVATION COMMISSION  
By [Signature]  
Title OIL & GAS INSPECTOR

