

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

October 25, 1950

Moument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Anarada Petroleum Corporation

State of N.M.

Well No. 1

in the

Company or Operator

Lease

C/NE/4 NE/4

of Sec. 26

T. 12-S

R. 33-E

N. M. P. M.,

Hightower

Field

Lea

County.

The dates of this work were as follows:

October 23, 1950

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on October 21,

1950

and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10189' - Total Depth - Line - Run Schlumberger Electrical & Gamma Ray Surveys. Spotted 35 sacks cement from 10189' to 10360', 35 sacks from 8690' to 8761', 35 sacks from 3990' to 3841' and 25 sacks from 2930' to 1950'. Out off 8-5/8" casing at 725' and recovered same. Spotted 50 sacks cement from 334' to 271' and dumped 10 sacks cement in top of 13-3/4" surface casing and set a piece of 4" Line Pipe, cemented in center of surface casing, extending 5' above surface of the ground. Heavy mud between all of the above plugs.

Witnessed by K. V. Stephenson

Anarada Petroleum Corporation

Foreman

Name

Company

Title

Subscribed and sworn before me this

25th day of October, 1950

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name

Position

Representing

Anarada Petroleum Corporation

Company or Operator

My commission expires 10-24-53

Address

Braver B, Moument, New Mexico

Remarks:

OCT 25 1950

Ray Garbrough
Oil & Gas Inspector
Name
Title