

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Form C-102

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Monument, New Mexico

December 13, 1951

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Amerada Petroleum Corporation State BTB Well No. 2 in C/SK/L, NM/L

Company or Operator
of Sec. 26, T. 12-S, R. 33-E, N. M. P. M., Lea Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

10225' T.D. 9050' Plug Back Depth - Lime. Finished drilling 6-3/4" hole at 2:10 PM, 12/8/51. Ran Drill Stem Test from 10198' to 10225'. Ran Schlumberger's Electrical, Gamma Ray & Microlog Surveys. Plugged back from 10225' to 9050' With Cement. Ran 5 1/2" Cg. as follows:

30 Jts	5 1/2" OD 17# N-80 R-3 8-RT SS C.g., LT&C New	1193.93'
46 Jts	17# J-55 R-3 8-RT German Cg. LT&C New	1655.37'
112 Jts	15.5# J-55 R-2 8-RT German Cg. RT&C New	3513.84'
39 Jts	17# J-55 R-3 8-RT German Cg. LT&C New	1330.11'
34 Jts	17# N-80 R-3 8-RT SS Cg., LT&C New	1343.82'
261 "		9037.07'

Casing set @ 9050' with 600 sacks Slo-Set Cement mixed 3% Jel and 1/4" Flo-Seal Per sack. Ran 7 Baker Centralizers spaced 30' apart from 8650' to 9035' and 14 weatherford scratchers spaced 15' apart in above section. After W.O.C. for approximately 24 hours we will test casing shut-off.

Approved. DEC 14 1951, 19
except at follows:

Amerada Petroleum Corporation
Company or Operator

By *E. J. Topp*
Position Assistant District Superintendent
Send communications regarding well to

Name Amerada Petroleum Corporation
Address Drawer D, Monument, New Mexico

OIL CONSERVATION COMMISSION,
By *Roy Guhring*
Title Oil & Gas Inspector