

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

RECEIVED

AUG 17 1950

OIL CONSERVATION COMMISSION

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

August 14, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation State NY #3 Well No. 1 in the Q/SE/4 NE/4 of Sec. 27, T. 12-S, R. 33-E, N. M. P. M., Hightower Field Lea County.

The dates of this work were as follows: August 13, 1950

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on August 11, 1950 and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9012' - Total Depth - Line. Ran Schlumberger's Electrical, Gamma Ray & Microlog Surveys. Potted 40 sacks of cement from 9012' to 8835', 50 sacks cement from 8834' to 8633', 25 sacks cement from 3670' to 3760' and 25 sacks cement from 1900' to 1990'. Cut off 7-5/8" Casing at 600' and recovered 15 lbs., 509.03' of same. Dumped 10 sacks cement in top of 11-3/4" surface casing and set a piece of 4" Line Pipe, cemented in center of surface casing, extending 5' above surface of ground. Heavy mud between all of the above plugs. Well plugged & abandoned at 10:00 P.M., August 13, 1950.

Witnessed by G. E. Nichols Amerada Petroleum Corporation Form 800  
Name Company Title

Subscribed and sworn before me this.....

14th day of August, 1950

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Dr. TappPosition Assistant District SuperintendentRepresenting Amerada Petroleum Corporation  
Company or OperatorMy commission expires 10-21-53Address Branch D, Monument, New Mexico

Remarks:

APPROVED  
AUG 17 1950  
Date

Roy Yudrolegk  
Name  
Chief Inspector  
Title