

Set 150' cement plug in bottom of well (9650-9500)

Set 150' cement plug near bottom of salt string; 75' below salt string & 75' up into salt string (4135' up to 3985).

Set 100' cement plug up to surface. All intervals between plugs filled with mud

Result ~~pipeliner's~~ laden fluid.

Set a 4" pipe marker in cement to extend 4' above ground level.

..... Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from surface feet to 9765 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Dry & Abandoned 10-29-1953

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....	
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt.....	T. Montoya.....	T. Farmington.....	
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....	
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....	
T. San Andres.....	T. Granite.....	T. Dakota.....	
T. Glorieta.....	T. Wolfeamp 9000' to 9010'	T. Morrison.....	
T. Drinkard.....	T. Permo Penn 9580	T. Penn.....	
T. Tubbs.....	T.	T.	
T. Abo.....	T.	T.	
T. Penn.....	T.	T.	
T. Miss.....	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	527	527	Caliche, sand, red bed, shale				
527	3189	2662	Blue shale, sand, red bed, gravel, anhy.				
3189	3971	782	Red shale, red bed, anhy., salt, gypsum.				
3971	4236	265	Anhy. red beds, lime.				
4236	5419	1183	Lime.				
5419	6812	1393	Lime Dolomite.				
6812	8125	1313	Lime, Dolo. shale, anhy. gypsum.				
8125	9701	1576	Shale, dolom, lime.				
9701	9765	64	Lime.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator The Ohio Oil Company Address Hobbs, New Mexico P. O. Box 2107
Name D. H. Burman Position or Title Superintendent
November 18, 1953 (Date)