

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. Copy will be returned to the sender on which will be given the approval, with any modifications considered advisable for approval by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. Additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOFebruary 17, 1953
(Place)Tatum, New Mexico
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation - Junious Tulk

(Company or Operator)

Well No. 1

in N

(Unit)

C/SR/

1/4

SW/

1/4 of Sec. 22

T

13-S

R

33-E

NMPM,

Lazy "J"

Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

10,495' - Total Depth. Line. Ran Drill Stem Test from 10,295' to 10,450'. No shows of oil or gas. Finished drilling 7-7/8" hole @ 5:45 AM, 2/16/53. Ran Schlumberger surveys. It is our intention to plug and abandon the above well. The following procedure will be followed: Spot 35 sacks regular cement from 9307' to 9194'; spot 35 sacks regular cement from 3983' to 3871'; run McGullough jet cutter and shoot off 8-5/8" casing @ 567'; salvage casing and spot 10 sacks regular cement in top of 13-3/8" casing. Hole will be filled with heavy drilling mud below and between cement plugs. A piece of 4" pipe will be cemented in top of 13-3/8" casing and will extend at least 5' above ground level to serve as marker.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy: Roy Gurthwaite
Title:Amerada Petroleum Corporation
Company or OperatorBy: V. J. Johnson
Position: Assistant District Superintendent

Send Communications regarding well to:

Name: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mexico

