

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)July 19, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Sinclair Oil & Gas Company** State **245** Well No. **1** in **1** (Unit)  
(Company or Operator) Lease  
**SE**  $\frac{1}{4}$  **NE**  $\frac{1}{4}$  of Sec. **28**, T. **13S**, R. **33E**, NMPM, **Lamy J** Pool  
(40-acre Subdivision)  
**Lin** County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

ID 9700'-FB 9647

5 1/2"OD Casing @ 9700'- Top Cement behind 5 1/2"OD Casing 7400'

@ 5/8"OD Casing @ 4021'- Top Cement behind @ 5/8"OD Casing Approx. 1400'

13 3/8"OD Casing @ 326'- Cement Circulated to surface.

Well not producing- after several workovers attempting to stimulate production

Fill Hole w/ heavy mud- Cover Perforations f/ 9488 to 9638' w/ 25 Sk. Cement f/ 9647 to 9647

Shoot off 5 1/2"OD Casing @ Approx. 7400'- Set 24 Sk. Cement plug f/ 7300' to 7500'

Pull 5 1/2"OD Casing- Set 25 Sk. cement plug in bottom of @ 5/8"OD Casing f/ 3900 to 4055-

Shoot off @ 5/8"OD Casing @ Approx. 1400' &amp; pull- Set 25 Sk. cement plug f/ 1375 to 1425'

Set 25 Sack Cement plug in bottom of 13 3/8"OD Casing f/ 325 to 330'

Set 4" "Regulation Marker" in bottom of cellar &amp; top of 13 3/8"OD Casing extending 4' above surface level in 15 Sk. cement, fill cellar level with surface- Plugged &amp; Abandoned.

Approved....., 19.....  
Except as follows:**Sinclair Oil & Gas Company**  
Company or Operator

By.....

Position..... **Dist. Supt.**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name **G. C. Salter, 520 E. Broadway, Hobbs, N.M.**

Title.....

Address.....

