

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-10137
7. Unit Agreement Name
8. Farm or Lease Name State 245
9. Well No. 5
10. Field and Pool, or Wildcat Lazy J - Penn.
12. County Lea

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Atlantic Richfield Company
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>28</u> TOWNSHIP <u>13-S</u> RANGE <u>33-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4244' Grd

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input checked="" type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input type="checkbox"/>
OTHER	<input type="checkbox"/>
ALTERING CASING	<input type="checkbox"/>
PLUG AND ABANDONMENT	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The 5½" casing collapsed and Reda pump became stuck in this well in December, 1969. Fishing operations were unsuccessful and remaining reserves did not justify repairs needed. After verbal approval from Mr. Ramey, we set a 75 sk Class "A" cement plug inside 5½" casing from 7833' to 8693'. We now propose to P & A well as follows: Pull 5½" and 8-5/8" casing strings as deep as possible. Set these cement plugs:

30 sx in & out of 5½" stub  
30 sx from 5350' to 5450' (Top of Glorieta @ 5392')  
30 sx in & out of 8-5/8" shoe at 4047'.  
30 sx in & out of 8-5/8" stub  
30 sx in 13-3/8" shoe at 320' and 10 sx in top of well

9#/gal gel mud will be used to spot plugs. Location will be cleared and levelled. 13-3/8" casing string will remain intact.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>A. D. Stetches</u>	TITLE <u>Dist. Drlg. Supervisor</u>	DATE <u>1-9-70</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>SUPERVISOR DISTRICT</u>	DATE <u>JAN 1 1970</u>
CONDITIONS OF APPROVAL, IF ANY:		