

Orig: & cc: OCC  
cc: FHR  
JTR  
FNEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 28, 1955  
(Date)Hobbs, New Mex 100  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company  
(Company or Operator)State #245  
(Lease)J. C. Grain Drilling Company  
(Contractor)

Well No. 6 in the NW 1/4 NE 1/4 of Sec. 33

T. 13 S, R. 33 E, NMPM, Larry J. Penn. Pool, Lea County.

The Dates of this work were as follows: 4-19,

Notice of intention to do the work (was) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 9700, set 5 1/2" OD casing @ 9698 and cemented with 250 sacks cement. Ran temperature survey which indicated top of cement back of 5 1/2" casing @ 8747' from surface. Let cement set 72 hours and tested casing with 1,000# pump pressure for 30 minutes before and after drilling plug. No decrease in pressure. Drilled cement plug to 9697'. PBTD 9697, Ran Gamma Ray & Neutron logs, perforated 5 1/2" casing W/4 jet shots per foot from 9602-12, 9626-44, 9662-74. Ran tubing, snubbed lead water, well flowed 3 hours @ 8 barrels per hour. Loaded hole W/300 barrels oil, acidized W/1,000 gallons of mud acid @ Maximum pressure of 1500#, well went on vacuum before treatment completed. Snubbed lead oil. Well flowed 180 barrels of new oil in 20 hours.

Witnessed by: Ira L. Wagner (Name) Sinclair Oil & Gas Co. (Company) Foreman (Title)

Approved: OIL CONSERVATION COMMISSION

*L. J. Stanley*  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *CC Smith*

Position: Dist. Supt.

Representing: Sinclair Oil &amp; Gas Company

Address: 520 East Broadway, Hobbs, New Mexico