Submit 3 Copies to Appropriate

## State of New Mexico

Form C-103

Energy, Minerals and Natural Resources Department Revised 1-1-89 <u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE [ DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. LG 2612 SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Saunders 10 State WELL X WELL 2. Name of Operator 8. Well No. MWJ PRODUCING COMPANY 2 3. Address of Operator 9. Pool name or Wildcat 400 W. Illinois - Suite 1100 Midland, Texas 7970 Saunders Permo Upper Pern 4. Well Location Unit Letter J: 1980 Feet From The South \_\_\_\_ Line and 1980 Feet From The East Section 10 14S 33E Range Township **NMPM** Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 42021 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: Perf "B" zone 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MI & RU PU. POOH w/rods & pump. Rel anchor catcher & POOH w/tbg & BHA. 12/7/89: RU Wedge W/L, ran & set CIBP @ 9880'. POOH, RD W/L. RIH w/SN, CO & tbg. Tagged plug, circ well w/230 bbls 2% KCL wtr. Spt'd 1000 gals 15% HCL 12/8/89: ac w/2% KCL wtr. RU W/L & perf'd "B" zone from 9808-9812', 9818-9822', 9830-9842' 2 SPF. RD W/L. Ran Baker Model R-3 pkr, SSN, CO & 295 jts 2-3/8" Buttress Thread tbg. Set pkr w/15000# tension & flanged up. End of pkr @ 9750', SN @ 9742'. L2/9/89: Swabbed l2/10-11: Shut down. 12/12/89: Ran redressed pkr, SN, CO & tbg. 12/13/89: Acd w/2000 gals 20% HCL ac & 50 7/8" 1.1 sp grav ball sealers @ 3.8 BPM Ball action to 5000 psi w/40 bbls flush. ISIP 1400 psi, @ 4250 psi. 3" vacuum. Swabbed. .2/14/89: Ran MA jt w/BP, perf sub, SSN, AC & 296 jts tbg (EOT @ 9809'). Ran pump I hereby certify that the last firmation above is true and complete to the best of my knowledge and belief. & rods, hung well on, RD & MO. Pat Drexler - Agent DATE 12/21/89 SIGNATURE . TYPE OR PRINT NAME

(This space for State CROCINAL SIGNED BY JERRY SEXTON

DISTRICT I SUPERVISOR

JAN 03 1990

APTROVED BY .....

RECEIVED

JAN 02 1990

MOBBS GFFICE