

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Rustler		Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1688	T. Canyon		T. Ojo Alamo	T. Penn. "D"
T. Salt		T. Strawn		T. Kirtland-Fruitland	T. Penn. "C"
D. Salt		T. Atoka		T. Pictured Cliffs	T. Penn. "D"
T. Yates	2648	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian		T. Menefee	T. Madison
T. Queen	3411	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya		T. Mancos	T. McCracken
T. San Andres	4069	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	5557	T. McKee		Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger		T. Dakota	
T. Blinberry		T. Gr. Wash		T. Morrison	
T. Tubb	6987	T. Granite		T. Todilto	
T. Drinkard		T. Delaware Sand		T. Entrada	
T. Abo	7712	T. Bone Springs		T. Wingate	
T. Wolfcamp LS	9099	T. XX Marker	9312	T. Chinle	
T. Penn.		T. Virgilian	9790	T. Permian	
T. Cisco (Bough C)		T. Bough C	9898	T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
SEE ORIGINAL FOR DEPTHS 0-6000'							
6000	6220	220	Dolomite, Sandstone				
6220	6840	620	Dolomite				
6840	7370	530	Dolomite, Chert				
7370	7620	250	Dolomite				
7620	8460	840	Dolomite, Anhydrite, Shale				
8460	8830	370	Dolomite, Shale, Chert				
8830	9100	270	Anhydrite, Dolomite				
9100	9380	280	Limestone				
9380	9760	380	Chert, Limestone, Shale				
9760	10250	490	Lime, Shale				

RECEIVED

APR 24 1985

C. C. D.
HOBBS OFFICE