## NEW MEXICO OIL CONSERVATION COMMUNICATION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below REPORT ON REPORT ON RESULT OF TEST REPORT ON BEGINNING REPAIRING WELL OF CASING SHUT-OFF DRILLING OPERATIONS REPORT ON RECOMPLETION REPORT ON REPORT ON RESULT I **OPERATION** (Other) OF PLUGGING WELL October 6, 1954 Midland, Texas Following is a report on the work done and the results obtained under the heading noted above at the MPMINY State of New Mexico "AT" The Texas Company Well No...... 2 in the SE 1/4 SE 1/4 of Sec. 10 14-S R 33-E NMPM, Wildcat Pool, Lea County. August 8, 1954 The Dates of this work were as follows: and approval of the proposed plan (was) (\*\*\*\*\*\*\*\*\*\*) obtained. DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED TD: 13,711' - Lime 13 3/8" set at 355". 8 5/8" set @ 42001. This well was drilled to a total depth of 13,711 without encountering any commercial shows of oil or gas; therefore, well was plugged and abandoned in Spotted the following cement plugs. the following manner: 50 sacks at 13,711' 30 sacks from 12790' to 12890' 30 sacks from 12010' to 12110' 30 sacks from 11495' to 11595' 150 sacks from 10000' to 10500' 30 sacks from 92481 to 7647° to 30 sacks from 6941' to 7041' (see back side) 30 sacks from Witnessed by....(Name) (Company) I hereby certify that the information given above is true and complete Approved: OM-CONSERVATION COMMISSION to the best of my knowledge Dist. Supt. Representing The Texas Company Box 1270, Midland, Texas (Date) (Title)

30 sacks from 5507° to 5507° 50 43.50°

Levelled location and set usual marker. This location is ready for your inspection.