

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Lovington, New Mexico

November 20, 1961

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation STATE S "J" Well No. **4** in **X**
(Company or Operator) (Unit)

SW $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **23**, T. **14-S**, R. **33-E**, NMPM., **Saunders** Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Pull 2-3/8" OD EUE Tubing packer & flow valves; Perforate 5-1/2" Csg liner from 9808' to 9812', 9824' to 9826', 9862' to 9864', 9870' to 9871', 9873' to 9875', 9878' to 9883', 9914' to 9929', with 2 bullet shots per foot,, Rerun 2-3/8" OD EUE Tubing with packer and Hydraulic holddown with flow valves and acidize 5-1/2" casing perforations OLD PERFORATIONS From 9765' to 9774', 9787' to 9791', and NEW PERF from 9808' to 9812', 9824' to 9826', 9862' to 9864', 9870' to 9871', 9873' to 9875', 9878' to 9883', with 5000 Gal 15% Spec LT Acid using 125 rubber ball sealers inj constantly during treatment. Casing will be loaded with gas pressure for treatment Kick well off & resume producing

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Amerada Petroleum Corporation
Company or Operator

By.....

Position..... **Foreman**
Send Communications regarding well to:

Name..... **Amerada Petroleum Corporation**Address..... **Box 636, Lovington, New Mexico**

