State of New Mexico Energy, Ainerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO.	
5. Indicate Type of Lease STATE	FEE 🗶
6. State Oil & Gas Lease No.	

DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088	5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	STATE FEE K
1000 IOU DIEGO NG., AMEG, INVI. 67410	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:	
OIL GAS WELL OTHER	C.L.
2. Name of Operator	Stevens 8. Well No.
Charles B. Gillespie, Jr.	7
3. Address of Operator	9. Pool name or Wildcat
P. O. Box 8 Midland, Texas 79702	
Unit Letter <u>G</u> : 1980 Feet From The North Line and	1980 Feet From The East Line
Section 33 Township 14S Range 33E	NMPM Lea County
4216' DF	
11. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILL	ING OPNS. PLUG AND ABANDONMENT X
PULL OR ALTER CASING CASING TEST AND	CEMENT JOB
OTHER: OTHER:	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in	solution estimated data of stancing any annual
work) SEE RULE 1103.	community estimated date by starting any proposed
9/28/89: Set cast iron bridge plug at 9700'.	
10/02/89: Ran 2 3/8" tubing to 9700', tagged plug.	
Mixed 10 ppg mud and displaced hole. Mixed and pu Mixed and pumped 25 sx cement at 7700°.	umped 10 sx cement at 9700'.
Mixed and pumped 25 sx cement at 4067'.	
10/03/89: lagged plug at 3960'.	
Cut off and pulled 8 5/8" from 804'.	
0/04/89: Mixed and pumped 50 sx cement at 850' across 8 5/8	3" casing stub.
Taggec plug at 742'.	
Mixed and pumped 75 sx cement at 360'. 0/05/89: Tagged plug at 261'.	
Mixed and pumped 10 sx cement at surface.	
Welded 4" marker to surface pipe, cleaned location	ı .
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SKINATURE Alla W. Janly me Production	Manager pate 3/5/90
TYPE OR PRINT NAME David W. Hastings	<u>тејерноне но(915)683-1</u> 76
(This space for State Use)	
Company Company	THE BUILDS MAY 2 THE
APPROVED BY CHALLES TO THE	DATE