

NUMBER		AS RECEIVED	
DISTRIBUTION			
SANTA FE			
FILE			
U.S.G.S.			
LAND OFFICE			
TRANSPORTER	OIL		
	GAS		
PERORATION OFFICE			
OPERATOR			

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE & Perf Addl Pay		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

January 9, 1962  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Gulf Oil Corporation** **Maud Saunders** Well No. **4** in **L**  
(Company or Operator) (Unit)  
**NW**  $\frac{1}{4}$  **SW**  $\frac{1}{4}$  of Sec. **34**, T. **14-S**, R. **33-E**, NMPM., **Saunders** Pool  
(40-acre Subdivision)  
**Lea Co.** County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 10,010'. PBTD 9980'.

It is proposed to mill out packer, perforate additional pay, acidize and install new packer.

1. Pull rods, pump and tubing.
2. Mill out Guiberson packer, using Baker's packer milling tool and clean out to bottom.
3. Run gauge ring to bottom then perforate casing with 2 HPF in following intervals: 9952-60', 9818-23' and IX 9790-9810'.
4. Run Baker retrievable BP and FB packer and straddle bottom perforations 9952-60'. Treat with 1500 gals 15% NE acid.
5. Raise straddle tools and straddle upper 2 sets of perfs 9790 - 9810' and 9818-23'. Treat with 3000 gals 15% NE acid, and approx 60-70 7/8" RCMB sealers. Inject balls continuously after first 500 gals acid. Pull straddle tools.
6. Set permanent type production packer approx 50' above top perfs then rerun tubing & down hole gas separator assy, rods and pump. Test & return well to production

Approved....., 19.....  
Except as follows:

**Gulf Oil Corporation**  
Company or Operator

By.....

Position **Area Production Manager**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name **Gulf Oil Corporation**

Title.....

Address **Box 2167, Hobbs, New Mexico**