

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Roswell, New Mexico
 (Place)

July 27, 1959
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company State A Well No. 8 in B
 (Company or Operator) Lease (Unit)

NW 1/4 NE 1/4 of Sec. 34, T-14-S, R-33-E, NMPM, Saunders Pool
 (40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

PROPOSED OPERATION:

1. Pull rods & pump. Kill well with lease oil & pull tubing.
2. Perforate 5 1/2" casing @ 9942' - 9946', 9930' - 9938', 9898' - 9902', 9874' - 9980', & 9862' - 9868' w/1-1/2" JSPP.
3. Run tubing open-ended with hookwall packer & side door choke assembly with straight through insert. Set packer @ 9960'.
4. Treat perforations below packer w/1500 gallons 15% acid. Swab test.
5. Pull straight through insert & run side door insert. Swab test perforations above packer.
6. Spot 1500 gallons 15% acid through side door, then maintain pressure on tubing with lease oil while pumping oil down casing to inject acid. Overflush w/10 BO. Swab test.
7. If tests indicate upper zones to be gassy, further work will be proposed as required. If zones test satisfactorily, pull tubing, side door assembly, and packer. Run production string and place on production.

Approved....., 19.....
 Except as follows:

Approved
 OIL CONSERVATION COMMISSION

By.....
 Title.....

Shell Oil Company
 Company or Operator

By..... R. A. Lowery Original Signed By B. A. LOWERY

Position..... District Exploitation Engineer
 Send Communications regarding well to:

Name..... Shell Oil Company

Address..... Box 245, Roswell, New Mexico