## OIL JONSERVATION COMMILGION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON LUELLS

AUG 2 1/ 1944

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within tendans after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and agreement to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

even though the work was witnessed by an agent of and sworn to before a notary public. See additiona		rt by checking belo		mmssion.
REPORT ON BEGINNING DRILLING OPERA-			EPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON I	PULLING OR OTHERW	ISE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON I	DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X			
	m	land, Texas,	August 28, 19	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:		Place	D	ate
Following is a report on the work done and the resumble Oil & Refining Company H.	ults obtain M. Sta	ned under the head	ling noted above at theWell No	
NE/4 of NW/4 of Sec. 1		T	31-5	, N. M. P. M.,
N/W Tatum Wildeat Field,		Lea		County.
The dates of this work were as follows: Augus	rt 26,	1944		-
Notice of intention to do the work was (was not) s	ubmitted	on Form C-102 on.	August 26	19 44
Plugged hole with cement from 4994° Plugged hole from 4700° to 4300° with	to 470	laden fluid.	icks Trinity Portl Plugged hole from	3300' to 32
Plugged hole with cament from 4994' Plugged hole from 4700' to 4300' with 255' sacks Portland cement. Picasing. Comented from 10' to surface	to 4700 h mad-	)' with 100 se laden fluid, ple with mud-1	icks Trinity Portl Plugged hole from inden fluid from 3	3300' to 32 250' to top
Plugged hole with cement from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Pertland cement. Fi casing. Cemented from 10' to surface regulation marker.	to 4700 h mad-	)' with 100 se laden fluid, ple with mud-1	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland cemen	3300' to 32 250' to top
Plugged hole with cament from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Portland cement. Fi casing. Cemented from 10' to surface regulation marker.	to 4700 th mmd-:	or with 100 seinden fluid.  ole with mud-l  5 sacks Trini	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland cemen	3300' to 3: 250' to top t with
Plugged hole with cement from 4994* Plugged hole from 4700° to 4300° wit with 255° sacks Portland cement. Fi casing. Cemented from 10° to surface regulation marker.  Witnessed by	to 4700 ih mad-;	company hereby swear or	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland comen	3300' to 32 250' to top t with
Plugged hole with cement from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Pertland cement. Fi casing. Cemented from 10' to surface regulation marker.  Witnessed by	to 4700 in made.	Company thereby swear or a strue and correct.	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland comen	3300' to 3: 250' to top t with
Plugged hole with cement from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Pertland cement. Fi casing. Cemented from 10' to surface regulation marker.  Witnessed by  Name  Subscribed and sworn before me this  28th day of August  Notary Public	to 4700 is mid-illed he with	Company thereby swear or a strue and correct.  Name Position Division	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland comen affirm that the informat a Superintendent able Oil & Refinin	3300° to 32 250° to top t with  Title  ion given above
Plugged hole with cement from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Pertland cement. Fi casing. Cemented from 10' to surface regulation marker.  Witnessed by  Name  Subscribed and sworn before me this  28th day of August , 1	to 4700 in mid-illed he with	Company Thereby swear or a strue and correct. Name Position Division Representing	acks Trinity Portli Plugged hole from inden fluid from 3 ity Portland comen affirm that the informat affirm that the informat	3300° to 3: 250° to top t with  Title ion given above
Plugged hole with cement from 4994' Plugged hole from 4700' to 4300' wit with 255' sacks Portland cement. Fi casing. Cemented from 10' to surface regulation marker.  Witnessed by  Name  Subscribed and sworn before me this  28th day of August  Notary Public Fillio Man Foresco	to 4700 in mid-illed he with	Company thereby swear or a strue and correct.  Name Position Division Representing	acks Trinity Portl Plugged hole from laden fluid from 3 ity Portland comen affirm that the informat a Superintendent able Oil & Refinia Company or Operator	3300° to 32 250° to top t with  Title  ion given above

## 

10 J