

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65
30-025-01836

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG - 6171	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Western States Producing Company		8. Farm or Lease Name Smelting State
3. Address of Operator 900 Building of the southwest - Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>12-S</u> RANGE <u>34-E</u> NMPM.		10. Field and Pool, or Wildcat East Bagley (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4178' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spotted 35 sx cement plug from 10,000' to 9700'.
- Shot off 5 1/2" casing at 8,406', spotted 50 sx cement plug at 8406 to 8200'
- Spotted 35 sx cement plug at 5540, Glorietta top , spotted 50 sx cement plug from 4250' to 4080' laid down 5 1/2" casing.
- Spotted 10 sx cement plug at surface in 9 5/8" casing and set dry hole marker.
- Cleaned and leveled cellar and location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Don C. Bennett TITLE Operations Manager DATE 9-30-70

APPROVED BY John W. Runyan TITLE Geologist DATE 10 28 1971

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

DEC 2 1970

OIL CONSERVATION COMM.
HOBBBS, N. H.