

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLYGordon M. Come, P. O. Box 1118, Lovington, New Mexico
(Company or Operator)

(Lease)

Well No. 2, in SW/4 SW/4 of Sec. 24, T. 12, R. 34 E, NMPM.

Undesignated (Ranger Lake Extension) Pool, Lea County.

Well is 330 feet from South line and 330 feet from West line

of Section 24. If State Land the Oil and Gas Lease No. is 3-2366-42

Drilling Commenced September 10, 1958 Drilling was Completed October 24, 1958

Name of Drilling Contractor McVay & Stafford Drilling Co.

Address 1112 Philtown, Tulsa 3, Oklahoma

Elevation above sea level at Top of Tubing Head 1140 feet. The information given is to be kept confidential until No, 19.

OIL SANDS OR ZONES

No. 1, from 10,310' to 10,321' No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from 10,345' to 10,375' feet salt water

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	Spiral Weld	New	345'	Halliburton			Surface String
8-5/8"	32 #	New	4240'	Halliburton			Intermediate Str.
5-1/2"	17#	New	10,375'	Saker	10,310.5' to		Production Str.

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15-1/2"	13-3/8"	345'	350	Halliburton		
11"	8-5/8"	4240'	1750	Halliburton		
7-7/8"	5-1/2"	10375'	350	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforated 10' interval with 40 jet shots.

Result of Production Stimulation 269 bbls. 15-1/2 hours.

Depth Cleaned Out.

CORD OF DRILL-STEM AND SPECIAL TI

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 10,175 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing November 5, 1958

OIL WELL: The production during the first 24 hours was 269 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 60 deg

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy.
T. Salt.
B. Salt.
T. Yates. 2835'
T. 7 Rivers.
T. Queen. 3560'
T. Grayburg.
T. San Andres. 4165'
T. Glorieta.
T. Drinkard.
T. Tubbs. 7060'
T. Abo. 7765'
T. Penn.
T. Miss.

T. Devonian.
T. Silurian.
T. Montoya.
T. Simpson.
T. McKee.
T. Ellenburger.
T. Gr. Wash.
T. Granite.
T. alfamp 9200'
T. say some 10,910'
T.
T.
T.

Northwestern New Mexico

T. Ojo Alamo.
T. Kirtland-Fruitland.
T. Farmington.
T. Pictured Cliffs.
T. Menefee.
T. Point Lookout.
T. Mancos.
T. Dakota.
T. Morrison.
T. Penn.
T.
T.
T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	200		Caliche, sand, redbed				
200	343		Redbed				
343	1244		Redbed				
1244	1997		Anhydrite & redbed				
1997	2164		Anhydrite				
2164	3017		Anhydrite & salt				
3017	4174		Anhydrite				
4174	4210		Anhydrite & lime				
4210	4240		Lime				
4240	7485		Lime				
7485	8275		Lime & shale				
8275	9547		Lime				
9547	9573		Lime & chert				
9573	10375 TD		Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator

Address

Name

Position or Title

Gordon M. Conner
GORDON M. CONNER
11/19/58
Box 1148, Lovington, N. M.
Operator